

Aitken Freeman Pty Ltd

Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com e-mail: sales@aitkenfreeman.com

MATERIAL SAFETY DATA SHEET - PAGE 1 OF 4

TECSEAL WB BASE

This product is classified as hazardous according to criteria of NOHSC

Section 1 – Identification of the Material and Supplier

PRODUCT (MATERIAL) NAME: TECSEAL WB BASE

OTHER NAMES: RECOMMENDED USES:

SUPPLIER NAME/ADDRESS:

TELEPHONE NUMBER: EMERGENCY PHONE NUMBER: (03) 9701 3955

Base component of a solvent free epoxy coating for concrete
Aitken Freeman Pty Ltd – Factory 7, 7-9 Brough St, Springvale VIC 3171
(03) 9701 3955 FACSIMILE NUMBER: (03) 9701 3956

HOURS: 0800-1700 Mon-Fri

Section 2 – Hazards Identification

POISONS SCHEDULE:

HAZARD CLASSIFICATION:

Classified as a HAZARDOUS SUBSTANCE according to criteria of NOHSC. Classified as NON DANGEROUS GOODS according to criteria of ADG Code.

RISK PHRASES:

R22: Harmful if swallowed

R41: Risk of serious damage to the eyes R43: May cause sensitisation by skin contact R37/R38: Irritating to respiratory system and skin1

SAFETY PHRASES:

S20: When using, do not eat or drink

\$23: Do not breathe vapour **\$24/25**: Avoid contact with skin and eyes

S28: After contact with skin, wash immediately with plenty of soap suds. **S36**: Wear suitable protective clothing **S38**: In case of insufficient ventilation, wear suitable respiratory equipment

Section 3 – Composition / Information on Ingredients

INGREDIENTS:

| Chemical Name: | Proportion: | CAS Number: | |
|------------------------------|-------------|-------------|--|
| Bisphenol A Resin | > 60 % | 25068-38-6 | |
| C12-C14 Alkyl glycidyl ether | 10 - 30 % | 68909-97-2 | |
| | | | |

Balance of formulation consists of ingredients below cut-off rates or ingredients determined not to be hazardous.

Section 4 – First Aid Measures

INHALATION: If inhaled, remove patient from contaminated area to fresh air. Lay patient down,

keep warm and rested. Encourage patient to blow nose and clear breathing passages. If not breathing, apply artificial respiration. Seek medical attention if

irritation persists

INGESTION: If swallowed, DO NOT induce vomiting. Rinse mouth with plenty of water. Seek

immediate medical advice from a doctor or the Poisons Information Centre

(13 11 26 Australia-wide).

If skin or hair contact occurs, remove all contaminated clothing and wash before SKTN:

reuse. Wash off skin and/or hair with running water and soap if available. Seek

medical assistance if irritation persists.

EYES: If product comes into contact with eyes, hold eyelids apart and flush the eye

continuously with fresh running water. If pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be

undertaken by skilled personnel.

FIRST AID FACILITIES:

Eye wash and normal washroom facilities.

Treat symptomatically. **POISON INFORMATION CENTRE** – 13 11 26 Australia-ADVICE TO DOCTOR:

wide.

MATERIAL SAFETY DATA SHEET - PAGE 2 OF 4

Section 5 – Fire Fighting Measures

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, foam or water fog

Wear breathing apparatus and gloves. Avoid bodily contact with substance or run-off. If significant quantity of this product is involved in a fire, contact the fire FIRE FIGHTING:

brigade.

FIRE / EXPLOSION HAZARD: This product is classified as a C1 combustible product. There is no risk of an

explosion from this product under normal circumstances if it is involved in a fire. Fire decomposition products from this product may be toxic if inhaled. Take

appropriate protective measures.

Section 6 – Accidental Release Measures

EMERGENCY PROCEDURES:

Product is slippery when spilt – avoid accidents by cleaning up any spills immediately. Wear gloves, protective goggles and appropriate protective equipment to avoid eye and skin contact. If significant chance that product vapours or mists are likely to build up in the spill area, a respirator should also be worn. Isolate and contain spill and soak up with inert material such as clay or cand. Provent by any many proscible the material from entering storm water. sand. Prevent by any means possible the material from entering storm water drains, waterways, basements or workpits. Collect in suitable containers and ensure these are correctly labelled. Ensure area is thoroughly ventilated before

recommencing work.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP:

Contain and collect spills as detailed above. Refer to State Land Waste Management Authority for disposal considerations.

Section 7 - Handling and Storage

PRECAUTIONS FOR SAFE HANDLING:

Wear protective goggles or face shield and rubber gloves and barrier cream to prevent eye and skin contamination. Contact lenses pose a special hazard as they may absorb irritants. Suitable protective clothing, PVC gloves and boots should be worn. Use in a well ventilated area, preferably outdoors. General exhaust is normally adequate. If risk of overexposure exists, wear SAA approved respirator.

CONDITIONS FOR SAFE STORAGE:

Keep containers tightly sealed when not in use. Store in a cool, dry, well

ventilated place out of direct sunlight. Keep away from strong acids, bases and

oxidising agents.

INCOMPATIBILITIES: No restrictions.

Section 8 - Exposure Controls / Personal Protection

NATIONAL EXPOSURE STANDARDS:

No exposure standards have been established for this product by NOHSC. Refer to limits for individual constituents listed below:

Bisphenol A epoxy resin – none assigned for material, but contains Epichlorohydrin: TLV TWA: 0.1ppm, 0.38mg/m³ – skin ES TWA: 0.1ppm, 0.4mg/m³

BIOLOGICAL LIMIT VALUES: ENGINEERING CONTROLS:

Not established for the product.

If used in limited ventilation, ensure adequate ventilation to maintained exposure levels are kept below standards, by using a local exhaust. Keep containers closed

when not in use. **PERSONAL PROTECTION:**

Avoid unnecessary contact as good work practice. Wash contaminated clothing and protective equipment before storing and reuse. Wash hands before eating,

smoking, or using the toilet.

RESPIRATORY PROTECTION:

It is usually safe not to use respiratory protection. However, where engineering controls are not effective in controlling airborne exposure, the use of a mask or other device is appropriate. For assistance in selecting suitable equipment consult AS/NZ1715.

EYE PROTECTION:

Eye protective measures are normally necessary, and are suggested when using this product. Consult AS1336 and AS/NZ1337.

Rubber, PVC or other protective gloves are necessary, and desirable, especially if

PROTECTIVE GLOVES:

this product is being used frequently or for lengthy periods. Consult AS2161 for

guidance.

CLOTHING:

Člean overalls should be worn, preferably with an apron. Consult AS2919 for

clothing guidance.

SAFETY FOOTWEAR:

Wearing safety boots is advisory. Consult AS/NZ2210 for advice on Occupational

Protective Footwear.

MATERIAL SAFETY DATA SHEET - PAGE 3 OF 4

Section 9 - Physical and Chemical Properties

APPEARANCE (COLOUR, PHYSICAL FORM, SHAPE):

Transparent liquid **ODOUR:** Nil

SOLUBILITY: Insoluble

VAPOUR DENSITY: Not available Negligible **VAPOUR PRESSURE: MELTING POINT:** Not applicable **BOILING POINT:** Not available FREEZING POINT: SPECIFIC GRAVITY: Not available 1.0 - 1.1**UPPER FLAMMABLE LIMIT:** Not established **FLASH POINT** > 93°C **AUTOIGNITION TEMPERATURE:**Unknown

LOWER FLAMMABLE LIMIT: Not established VOLATILE ORGANIC COMPOUNDS (VOC) CONTENT: No data available

Section 10 - Stability and Reactivity

CHEMICAL STABILITY: CONDITIONS TO AVOID:

Keep away from strong acids, bases and oxidising agents.

No restrictions INCOMPATIBLE MATERIALS: **HAZARDOUS DECOMPOSITION PRODUCTS:**

On burning may emit toxic fumes, including carbon and nitrogen oxides.

HAZARDOUS REACTIONS:

Section 11 - Toxicological Information

TOXICOLOGY INFORMATION: No toxicity data is available for this product.

HEALTH EFFECTS FROM THE LIKELY ROUTES OF EXPOSURE:

INHALATION: Not normally a hazard at normal temperatures, however at elevated

temperatures vapour may be irritating to respiratory system. Inhalation of

vapour may result in nausea and headache.

INGESTION: Swallowing may result in nausea, vomiting, abdominal pain and diarrhoea.

SKIN: Is irritating and may cause drying of the skin. May lead to dermatitis and in some

cases sensitisation. The material may accentuate pre-existing skin conditions.

EYES: Irritating and abrasive to the eyes and is capable of causing temporary

impairment of vision, eye inflammation and ulceration.

CHRONIC EFFECTS: May causes sensitisation in susceptible individuals by skin contact. Repeated or prolonged skin contact may result in allergic contact dermatitis.

Section 12 – Ecological Information

Not available

PERSISTENCE AND DEGRADIBILITY:

Not available **MOBILITY** Not available

ENVIRONMENTAL PROTECTION:

Product is biodegradable and will not accumulate in soil or water or cause long

term problems.

Section 13 – Disposal Considerations

Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus after admixture with suitable combustible material) Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed. Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Section 14 - Transport Information

This material is a Non Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

UN NUMBER: None assigned **UN PROPER SHIPPING NAME:** None assigned **DANGEROUS GOODS CLASS:** None assigned SUBSIDIARY RISK: None assigned **PACKING GROUP:** None assigned

SPECIAL PRECAUTIONS PER USER: Keep containers tightly sealed, store in a cool, dry, well ventilated place out of

direct sunlight. Keep away from strong acids, bases and oxidising agents.

HAZCHEM CODE: None assigned

Material Safety Data Sheet - Tecseal WB Base - Page 3 of 4 - Review Date 1st April 2016

MATERIAL SAFETY DATA SHEET - PAGE 4 OF 4

Section 15 - Regulatory Information

POISON SCHEDULE: S5

OHS: Unregulated ENVIRONMENTAL: Unregulated

ADDITIONAL NATIONAL AND/OR INTERNATIONAL REGULATORY INFORMATION:

Unregulated

Section 16 - Other Information

DATE OF PREPARATION OR LAST REVISION OF MSDS:

1st April 2016

CONTACT POINT: Aitken Freeman Pty Ltd

(03) 9701 3955

LITERATURE REFERENCES / SOURCES OF DATA:


Material Safety Data Sheets from Suppliers

List of Designated Substances - Worksafe Australia (on-line)

Australian Dangerous Goods Code 6th Edition

Standard for the Uniform Scheduling of Drugs and Poisons No 19

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of seller's knowledge, however seller makes no warranty whatsoever, expressed, implied, or of merchantability regarding to the accuracy of such data or the results to be obtained from the use thereof. Seller assumes no responsibility for injury to the buyer or third persons or for any damage to property. Buyer assumes all risks.



Aitken Freeman Pty Ltd

Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com e-mail: sales@aitkenfreeman.com

MATERIAL SAFETY DATA SHEET - PAGE 1 OF 4

TECSEAL WB HARDENER

This product is classified as hazardous according to criteria of NOHSC

Section 1 – Identification of the Material and Supplier

PRODUCT (MATERIAL) NAME: TECSEAL WB HARDENER

OTHER NAMES:

RECOMMENDED USES: SUPPLIER NAME/ADDRESS:

TELEPHONE NUMBER: **EMERGENCY PHONE NUMBER:** (03) 9701 3955

Hardener component of a solvent free epoxy coating for concrete

Aitken Freeman Pty Ltd – Factory 7, 7-9 Brough St, Springvale VIC 3171 (03) 9701 3955 FACSIMILE NUMBER: (03) 9701 3956 (03) 9701 3955 **HOURS:** 0800-1700 Mon-Fri

Section 2 – Hazards Identification

POISONS SCHEDULE:

HAZARD CLASSIFICATION:

Classified as a HAZARDOUS SUBSTANCE according to criteria of NOHSC. Classified as NON DANGEROUS GOODS according to criteria of ADG Code.

RISK PHRASES: R20/21/22: Harmful by inhalation, by contact with skin or if swallowed

R43: May cause sensitisation by skin contact

R36/37/R38: Irritating to eyes, respiratory system and skin

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in

the aquatic environment. **SAFETY PHRASES: S20**: When using, do not eat or drink

S23: Do not breathe vapour

S24/25: Avoid contact with skin and eyes

S28: After contact with skin, wash immediately with plenty of soap suds.

\$36: Wear suitable protective clothing

S38: In case of insufficient ventilation, wear suitable respiratory equipment

Section 3 – Composition / Information on Ingredients

INGREDIENTS:

| Chemical Name: | Proportion: | CAS Number: |
|--------------------------------------------|-------------|-------------|
| 3,6,9,12-Tetraazatetradecane-1, 14-diamine | < 2% | 4067-16-7 |
| Non hazardous ingredients | > 98% | |
| | | |

Balance of formulation consists of ingredients below cut-off rates or ingredients determined not to be hazardous.

Section 4 – First Aid Measures

INHALATION: If inhaled, remove patient from contaminated area to fresh air. Lay patient down,

keep warm and rested. Encourage patient to blow nose and clear breathing passages. If not breathing, apply artificial respiration. Seek medical attention if

irritation persists

INGESTION: If swallowed, DO NOT induce vomiting. Rinse mouth with plenty of water. Seek

immediate medical advice from a doctor or the Poisons Information Centre

(13 11 26 Australia-wide).

SKIN: If skin or hair contact occurs, remove all contaminated clothing and wash before reuse. Wash off skin and/or hair with running water and soap if available. Seek

medical assistance if irritation persists.

EYES: If product comes into contact with eyes, hold eyelids apart and flush the eye

continuously with fresh running water. If pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be

undertaken by skilled personnel.

FIRST AID FACILITIES: Eye wash and normal washroom facilities.

Treat symptomatically. POISON INFORMATION CENTRE - 13 11 26 Australia-**ADVICE TO DOCTOR:**

wide.

MATERIAL SAFETY DATA SHEET - PAGE 2 OF 4

Section 5 - Fire Fighting Measures

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, foam or water fog

FIRE FIGHTING: Wear breathing apparatus and gloves. Avoid bodily contact with substance or run-off. If significant quantity of this product is involved in a fire, contact the fire

FIRE / EXPLOSION HAZARD: This product is classified as flammable. There is no risk of an explosion from this

product under normal circumstances if it is involved in a fire. Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective

Section 6 - Accidental Release Measures

EMERGENCY PROCEDURES: Product is slippery when spilt - avoid accidents by cleaning up any spills

immediately. Wear gloves, protective goggles and appropriate protective equipment to avoid eye and skin contact. If significant chance that product vapours or mists are likely to build up in the spill area, a respirator should also be worn. Isolate and contain spill and soak up with inert material such as clay or sand. Prevent by any means possible the material from entering storm water drains, waterways, basements or workpits. Collect in suitable containers and ensure these are correctly labelled. Ensure area is thoroughly ventilated before

recommencing work.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP:

Contain and collect spills as detailed above. Refer to State Land Waste

Management Authority for disposal considerations.

Section 7 - Handling and Storage

PRECAUTIONS FOR SAFE HANDLING:

Wear protective goggles or face shield and rubber gloves and barrier cream to prevent eye and skin contamination. Contact lenses pose a special hazard as they may absorb irritants. Suitable protective clothing, PVC gloves and boots should be worn. Use in a well ventilated area, preferably outdoors. General exhaust is normally adequate. If risk of overexposure exists, wear SAA approved dust

respirator.

CONDITIONS FOR SAFE STORAGE:

Keep containers tightly sealed when not in use. Store in a cool, dry, well

ventilated place out of direct sunlight. Keep away from strong acids, bases and

oxidising agents.

INCOMPATIBILITIES: No restrictions

Section 8 - Exposure Controls / Personal Protection

NATIONAL EXPOSURE STANDARDS:

No exposure standards have been established for this product or its constituents

by NOHSC.

BIOLOGICAL LIMIT VALUES: Not established for the product.

If used in limited ventilation, ensure adequate ventilation to maintained exposure levels are kept below standards, by using a local exhaust. Keep containers closed **ENGINEERING CONTROLS:**

when not in use.

Avoid unnecessary contact as good work practice. Wash contaminated clothing PERSONAL PROTECTION:

and protective equipment before storing and reuse. Wash hands before eating,

smoking, or using the toilet.

RESPIRATORY PROTECTION:

It is usually safe not to use respiratory protection. However, where engineering controls are not effective in controlling airborne exposure, the use of a mask or other device is appropriate. For assistance in selecting suitable equipment consult

AS/N71715.

Eye protective measures are normally necessary, and are suggested when using this product. Consult AS1336 and AS/NZ1337. **EYE PROTECTION:**

PROTECTIVE GLOVES: Rubber, PVC or other protective gloves are necessary, and desirable, especially if

this product is being used frequently or for lengthy periods. Consult AS2161 for

guidance.

CLOTHING: Clean overalls should be worn, preferably with an apron. Consult AS2919 for

clothing guidance.

SAFETY FOOTWEAR: Wearing safety boots is advisory. Consult AS/NZ2210 for advice on Occupational

Protective Footwear.

MATERIAL SAFETY DATA SHEET - PAGE 3 OF 4

Section 9 - Physical and Chemical Properties

APPEARANCE (COLOUR, PHYSICAL FORM, SHAPE):

Transparent (or pigmented) liquid

Strong amine odour **ODOUR:** SOLUBILITY: Partially soluble

VAPOUR DENSITY: Not available **VAPOUR PRESSURE:** 1.0kPa at 20°C **BOILING POINT: MELTING POINT:** Not applicable >100°C at 100kPa SPECIFIC GRAVITY: FREEZING POINT: Not available 1.25

FLASH POINT: > 110°C **UPPER FLAMMABLE LIMIT:** Not established **LOWER FLAMMABLE LIMIT:** Not established **AUTOIGNITION TEMPERATURE: Unknown**

VOLATILE ORGANIC COMPOUNDS (VOC) CONTENT: No data available

Section 10 – Stability and Reactivity

Stable under normal conditions

CHEMICAL STABILITY: CONDITIONS TO AVOID: Keep away from strong acids and oxidising agents.

INCOMPATIBLE MATERIALS: No restrictions **HAZARDOUS DECOMPOSITION PRODUCTS:**

On burning may emit toxic fumes, including carbon monoxide, amines, ammonia

and nitrogen oxides.

HAZARDOUS REACTIONS: None

Section 11 – Toxicological Information

TOXICOLOGY INFORMATION: No toxicity data is available for this product.

HEALTH EFFECTS FROM THE LIKELY ROUTES OF EXPOSURE:

INHALATION: Vapour or mist is irritating to the upper respiratory tract and may cause

> sensitisation. Inhalation of vapour may aggravate pre-existing conditions such as asthma, bronchitis or emphysema. Acute effects may be chest and nasal irritation with coughing, sneezing, headache and nausea. Hazard increases at elevated

temperatures.

INGESTION: Harmful and highly irritating if swallowed. Swallowing may result in nausea,

> vomiting, abdominal pain and diarrhoea. May cause chemical burns to the mouth, throat and oseophagus, with extreme discomfort and pain. Considered an unlikely

route of entry in commercial/industrial environments.

SKIN: Prolonged exposure is highly irritating and may cause drying and cracking of the

skin. Material is corrosive and can cause chemical burns. Capable of causing dermatitis and sensitisation resulting in hives, rash, itching or swelling of extremities. Toxic effects may result from skin absorption. Sensitisation may appear after repeated symptom-free exposures. Open cuts, abraded or irritated skin should not be exposed to this material. This material may accentuate pre-

existing skin conditions.

FYFS: Highly irritating to the eyes and is capable of causing pain and corneal burns. If

not promptly treated, can lead to permanent eye injury.

CHRONIC EFFECTS: May causes sensitisation in susceptible individuals by skin contact or inhalation.

Repeated or prolonged skin contact may result in allergic contact dermatitis.

Section 12 - Ecological Information

ECOTOXICITY: Not available

PERSISTENCE AND DEGRADIBILITY:

Not available Not available

ENVIRONMENTAL PROTECTION:

Product is toxic to aquatic organisms, and may cause long-term adverse effects

in the aquatic environment. Avoid contaminating waterways.

Section 13 – Disposal Considerations

Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus after admixture with suitable combustible material) Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed. Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

MATERIAL SAFETY DATA SHEET - PAGE 4 OF 4

Section 14 - Transport Information

This material is a Non Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

UN NUMBER:
UN PROPER SHIPPING NAME:
DANGEROUS GOODS CLASS:
SUBSIDIARY RISK:
PACKING GROUP:
None assigned
None assigned
None assigned

SPECIAL PRECAUTIONS PER USER:

Keep containers tightly sealed, store in a cool, dry, well ventilated place out of

direct sunlight. Keep away from strong acids, bases and oxidising agents.

HAZCHEM CODE: None assigned

Section 15 – Regulatory Information

POISON SCHEDULE: S5

OHS: Unregulated ENVIRONMENTAL: Unregulated

ADDITIONAL NATIONAL AND/OR INTERNATIONAL REGULATORY INFORMATION:

Unregulated

Section 16 - Other Information

DATE OF PREPARATION OR LAST REVISION OF MSDS:

CONTACT POINT:

1st April 2016
Aitken Freeman Pty Ltd
(03) 9701 3955

LITERATURE REFERENCES / SOURCES OF DATA:

Material Safety Data Sheets from Suppliers

List of Designated Substances - Worksafe Australia (on-line)

Australian Dangerous Goods Code 6th Edition

Standard for the Uniform Scheduling of Drugs and Poisons No 19

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of seller's knowledge, however seller makes no warranty whatsoever, expressed, implied, or of merchantability regarding to the accuracy of such data or the results to be obtained from the use thereof. Seller assumes no responsibility for injury to the buyer or third persons or for any damage to property. Buyer assumes all risks.