



SAFETY DATA SHEET

ROOF & GUTTER SILICONE PREMIUM GREY
Revision Number 4.02

Revision date 20-Nov-2022
Supersedes Date: 11-Nov-2019

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name ROOF & GUTTER SILICONE PREMIUM GREY

Product Code(s)

30840060
30840060

Other means of identification

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Sealant

Uses advised against No information available

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity (single exposure)	Category 2

Label elements

Health hazard



SAFETY DATA SHEET

ROOF & GUTTER SILICONE PREMIUM GREY
Revision Number 4.02

Revision date 20-Nov-2022
Supersedes Date: 11-Nov-2019

Signal word

WARNING

Hazard statements

H351 - Suspected of causing cancer
H371 - May cause damage to organs

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/clothing and eye/face protection
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF exposed or concerned: Call a POISON CENTER or doctor

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.
Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number Not applicable 6

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
2-Butanone, O,O',O''-(methylsilylidyne)trioxime	22984-54-9	0 - <10
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	0 - <10
2-Butanone, oxime	96-29-7	0 - <10
Toluene	108-88-3	0 - <10
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

SAFETY DATA SHEET

ROOF & GUTTER SILICONE PREMIUM GREY
Revision Number 4.02

Revision date 20-Nov-2022
Supersedes Date: 11-Nov-2019

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact Wash off immediately with plenty of water for at least 15 minutes. If symptoms persist, call a physician.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms None known.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable extinguishing media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous combustion products Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Silicon oxides.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

SAFETY DATA SHEET

ROOF & GUTTER SILICONE PREMIUM GREY
Revision Number 4.02

Revision date 20-Nov-2022
Supersedes Date: 11-Nov-2019

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feeding stuffs.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

Incompatible materials Strong oxidizing agents.

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Chemical name	Australia
Toluene 108-88-3	TWA: 50 ppm TWA: 191 mg/m ³ STEL: 150 ppm STEL: 574 mg/m ³

OEL as published by Safe Work Australia

Biological occupational exposure limits

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection No special protective equipment required.

Skin and body protection Wear suitable protective clothing.

Hand protection Wear suitable gloves.

Respiratory protection Organic gases and vapors filter conforming to EN 14387. White. Brown.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Paste / Gel Liquid
Appearance Very viscous Paste
Color Gray

SAFETY DATA SHEET

ROOF & GUTTER SILICONE PREMIUM GREY
Revision Number 4.02

Revision date 20-Nov-2022
Supersedes Date: 11-Nov-2019

Odor	Organic	
Odor threshold	No information available	
Property	Values	Remarks • Method
pH	.	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	No data available	
Flash point	No data available	
Evaporation rate	No data available	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	
Relative vapor density	No data available	
Relative density	No data available	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	150000 - 250000 mPa s	@ 23 °C
Explosive properties	No information available	
Oxidizing properties	No information available	
Other information		
Solid content (%)	No information available	
Liquid Density	No information available	
VOC content		No information available

Section 10: Stability and reactivity

Reactivity

Reactivity Product cures with moisture.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

SAFETY DATA SHEET

ROOF & GUTTER SILICONE PREMIUM GREY
Revision Number 4.02

Revision date 20-Nov-2022
Supersedes Date: 11-Nov-2019

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Methyl alcohol. May emit toxic fumes under fire conditions. Carbon oxides. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document
ATEmix (dermal) 27,711.50 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butanone, O,O',O''-(methylsilylidyne)trioxime	LD50 = 2463 mg/Kg (Rattus) (OECD 401)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	-
N-(3-(trimethoxysilyl)propyl)ethylenediamine	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol) 1.5 - 2.44 mg/L air
2-Butanone, oxime	=100 mg/kg (ATE)	1000 - 1800 mg/kg (Oryctolagus cuniculus)	>4.83 mg/L (Rattus) 4 h
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Component Information					
Toluene (108-88-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.4	Rabbit	Dermal			Irritant

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

SAFETY DATA SHEET

ROOF & GUTTER SILICONE PREMIUM GREY
Revision Number 4.02

Revision date 20-Nov-2022
Supersedes Date: 11-Nov-2019

Component Information			
Toluene (108-88-3)			
Method	Species	Exposure route	Results
Regulation (EC) No. 440/2008, Annex, B.6 (Maximization test)	Guinea pig		No sensitization responses were observed

Germ cell mutagenicity No information available.

Component Information		
Toluene (108-88-3)		
Method	Species	Results
Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)	Salmonella typhimurium	Not mutagenic
OECD Test No. 476: In vitro Mammalian Cell Gene Mutation Test	Mouse	Not mutagenic

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
2-Butanone, oxime 96-29-7	Carc. 2	Carc. 1B	
Toluene 108-88-3			Group 3

Legend

IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans

Component Information		
2-Butanone, oxime (96-29-7)		
Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Reproductive toxicity No information available.

Component Information		
Toluene (108-88-3)		
Method	Species	Results
OECD 407	in vivo	Reproductive toxicant

STOT - single exposure Based on the classification criteria of the Globally Harmonized System as adopted in the country or region with which this safety data sheet complies, this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). May cause damage to organs.

STOT - repeated exposure No information available.

Component Information		
Toluene (108-88-3)		

SAFETY DATA SHEET

ROOF & GUTTER SILICONE PREMIUM GREY
Revision Number 4.02

Revision date 20-Nov-2022
Supersedes Date: 11-Nov-2019

Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.26	Rat, male, female	Oral		91 days	NOAEL: 625 mg/kg
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat, male, female	Inhalation, vapor			NOAEL: 1.131 mg/l

Aspiration hazard No information available.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
2-Butanone, O,O',O''-(methylsilylidyne)trioxime 22984-54-9	EC50 (72h) = 94 mg/L (Pseudokirchneriella subcapitata) OECD 201	EC50 (96h) >120 mg/L (Oncorhynchus mykiss) Freshwater static (OECD guideline 203)	-	EC50 (48h) > 120 mg/L (Daphnia magna) OECD 202
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio) Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static
2-Butanone, oxime 96-29-7	EC50: =83mg/L (72h, Desmodesmus subspicatus)	LC50: =760mg/L (96h, Poecilia reticulata) LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: 320 - 1000mg/L (96h, Leuciscus idus)	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	EC50: =750mg/L (48h, Daphnia magna)
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)

Persistence and degradability

Persistence and degradability Not readily biodegradable. Product cures with moisture.

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
2-Butanone, O,O',O''-(methylsilylidyne)trioxime 22984-54-9	1.69
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-0.3
2-Butanone, oxime 96-29-7	0.65
Toluene 108-88-3	3.93

SAFETY DATA SHEET

ROOF & GUTTER SILICONE PREMIUM GREY
Revision Number 4.02

Revision date 20-Nov-2022
Supersedes Date: 11-Nov-2019

Mobility

Mobility in soil No information available.

Mobility Insoluble in water.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

Section 14: Transport information

ADG Not regulated

IATA Not regulated

IMDG Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number Not applicable 6

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Toluene 108-88-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

AIC Listed

NZIoC Listed

SAFETY DATA SHEET

ROOF & GUTTER SILICONE PREMIUM GREY
Revision Number 4.02

Revision date 20-Nov-2022
Supersedes Date: 11-Nov-2019

ENCS	Not Listed
IECSC	Not Listed
KECL	Not Listed
PICCS	Listed

Legend:

AIIC - Australian Inventory of Industrial Chemicals
NZIoC - New Zealand Inventory of Chemicals
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 20-Nov-2022

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

SAFETY DATA SHEET

ROOF & GUTTER SILICONE PREMIUM GREY
Revision Number 4.02

Revision date 20-Nov-2022
Supersedes Date: 11-Nov-2019

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet