

Material Safety Data Sheet

Section 1:	Identification of Product & Supplier
Product:	Megapoxy PM - Part B (Use in conjunction with Megapoxy PM - Part A)
Classification:	Hazardous according to criteria of Worksafe Australia
Uses:	Adhesive for civil engineering use, tiling etc.
Supplier:	Vivacity Engineering Pty Ltd
ABN:	78 305 545 664
Street Address:	3 Sefton Road Thornleigh, NSW 2120, Australia
Telephone:	61 2 9875 3044
Facsimile:	61 2 9875 3665
Emergency Phone:	61 2 9484 7958 or 0418 112 515
e mail:	info@megapoxy.com

Section 2:	Hazards Identification
Hazard Category:	Xn Harmful, Xi Irritant
Risk Phrases:	R21/22 Harmful in contact with skin and if swallowed R43 May cause sensitisation by skin contact.
D.G. Class:	Not classified as dangerous goods
Subsidiary Risk:	Nil
Poison Schedule:	S 5
This product is a Schedule Poison S 5 and must be stored, maintained and used in accordance with the relevant regulation.	

Section 3:	Composition & Information on ingredients																		
Ingredients:	<table><thead><tr><th>Name</th><th>Cas No.</th><th>Proportion</th></tr></thead><tbody><tr><td>Polyaminoamide</td><td>68082-29-1</td><td>High</td></tr><tr><td>Tris-2,4,6 (Dimethylaminomethyl</td><td></td><td></td></tr><tr><td>Phenol</td><td>90-72-2</td><td>Low</td></tr><tr><td>Other ingredients determined</td><td></td><td></td></tr><tr><td>not to be hazardous</td><td></td><td>To 100 %</td></tr></tbody></table>	Name	Cas No.	Proportion	Polyaminoamide	68082-29-1	High	Tris-2,4,6 (Dimethylaminomethyl			Phenol	90-72-2	Low	Other ingredients determined			not to be hazardous		To 100 %
Name	Cas No.	Proportion																	
Polyaminoamide	68082-29-1	High																	
Tris-2,4,6 (Dimethylaminomethyl																			
Phenol	90-72-2	Low																	
Other ingredients determined																			
not to be hazardous		To 100 %																	
V.High >60, High 30 - 60, Med 10 - 29, Low 1 - 9, V.Low <1																			
All the constituents of this product are listed on the Australian Inventory of Chemical Substances (AICS) and National Registration Authority (NRA) approved active constituents.																			

Section 4:**First Aid Measures**

Poison Information Centres in each State capital can provide additional

Megapoxy PM - Part B

assistance for scheduled poisons. (Phone Australia 131 126)

Ingestion: If swallowed do not induce vomiting. Rinse mouth with water, give glass of water and seek medical attention.

Eye contact: Immediately irrigate with copious quantities of water for at least 15 minutes. Eyelids to be held open. Seek immediate medical assistance.

Skin contact: Remove contaminated clothing and footwear. Wash skin thoroughly with water. If swelling, redness, blistering or irritation occurs seek medical attention.

Inhalation: Remove victim from exposure to fresh air. If breathing difficulty, apply artificial respiration and seek medical attention.

Note to Physician: Treat the patient symptomatically.

Section 5:**Fire Fighting Measures**

Extinguishing media: Water, Foam, Dry chemical powder, Carbon dioxide.

Specific Hazards: The material is stable under normal conditions. Hazardous polymerisation can occur on heating. On decomposition gives off carbon dioxide, carbon monoxide, oxides of nitrogen, volatile amines and ammonia. Wear full protective clothing.

Fire Fighters: Wear positive pressure, self-contained breathing apparatus and full protective clothing.

Section 6:**Accidental Release Measures**

Small Spills: Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soil, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes.

Large Spills: Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soil, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes. If contamination of crops, waterways, drains or sewerage has occurred, advise Emergency Services or State Department of Agriculture.

Section 7:	Handling and Storage
-------------------	-----------------------------

Storage: Store in the closed, original container in a cool ventilated area. Keep containers tightly closed when not in use. Keep away from explosives, food, oxidising agents and organic peroxides. This product is a Scheduled Poison

Megapoxy PM - Part B

S5 and must be stored, maintained and used in accordance with the relevant regulations. Avoid from physical damage.

Section 8:	Exposure Controls & Personal Protection
-------------------	--

Exposure Limits: No value assigned for this specific product by the National Occupational and Safety Commission (Worksafe Australia). However, supplier recommended Hygiene Standard as under;

TWA STEL Carcinogen Notices

Material	TWA		STEL		Notices
	ppm	mg/m3	ppm	mg/m3	
Polyaminoamide	N/E*	N/E*	N/E*	N/E*	-
Tris-2,4,6 (Dimethyl-aminomethyl) Phenol	N/E*	N/E*	N/E*	N/E*	-

N/E* - No Exposure Standard has been established for this product.

Eng. Controls: Special ventilation is not normally required due to the low volatility of the product at normal temperature. However, in the operation of certain equipment or at elevated temperatures, mists or vapours may be generated and exhaust ventilation should be provided to maintain airborne concentration levels below the exposure standards or where no exposure standard is allocated, as low as reasonably practicable.

Personal Protection: Use overalls, safety shoes, safety goggles, rubber or chemical resistance gloves and respirator if required.

Manufacturing, Avoid skin and eye contact and the inhalation of vapour. Wear overalls, safety

Packaging & goggles and impervious gloves. Available information suggests that the gloves

Transport: made from PVC should be suitable for intermittent contact. However due to variations in glove construction and local conditions, the final assessment should be made by the user. If inhalation risk exists, wear organic vapour respirator meeting requirements of AS/NZS 1715 and 1716. Always wash hands with soap and water before smoking, eating, drinking or using toilet facilities.

Preparations & use Repeated exposure may cause allergic disorders. Sensitive workers should

of product: use protective clothing. Avoid contact with eyes and skin. Do not inhale mist or vapours. After each day's use, wash gloves, safety goggles and all the contaminated clothing.

Section 9:	Physical & Chemical Properties
-------------------	---

Appearance	Buff/Dark grey paste
Solubility	Partially soluble in water
Specific Gravity	1.3 - 1.4 @ 25 DEG. C
Megapoxy PM - Part B	
Boiling Point	More than 200 deg. C
Rel.Vapour Density (air=1)	> 1
Melting Range	Not established
Vapour Pressure (20o C)	Less than 0.01 Pa
Decomposition Temp.(o C)	More than 200 deg. C
Flash Point (o C)	More than 200 deg. C (ASTM D 93)
Flammability Limits (%)	Not established
Ph	Not applicable
Autoignition Temp. (o C)	Not available
% Volatile by Volume	Nil

(All above values are Typical Values only)

Section 10:	Stability & Reactivity
--------------------	-----------------------------------

Stability: The product is stable under normal conditions and use.

Section 11:	Toxicological Information
--------------------	----------------------------------

No adverse health effects are expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms that may arise if the product is mishandled are:

Acute Effects: Ingestion: Harmfull if swallowed. May cause gastrointestinal discomfort and irritation.

Eye: Brief contact may cause mild irritation to eyes.

Skin: Mild irritant and poorly absorbed through the skin. Prolonged and repeated contact may cause sever irritation and/or dermatitis

Inhaled: Not hazardous at ambient temperatures. Vapours generated at elevated temperatures or when inhaled repeatedly may cause irritation to nose, throat and respiratory tract.

Long Term Effects: Repeated skin contact and inhalation may result in sensitisation in some individuals. May cause allergic reaction, dermatitis or asthma like symptoms. Follow good working practice. Avoid ingestion, inhalation, eye and skin contact. Wash hands with soap and water before eating, drinking, smoking or using toilet facilities.

Acute & Chronic Negative in a battery of mutagenicity assays.

Toxicity: No evidence of carcinogenicity was observed in long term studies of rats. No developmental nor reproductive effects in rat and rabbit. Acceptable Daily Intake (ADI) for humans is 0.01 mg/kg/day.

Section 12:	Ecological Information
--------------------	-------------------------------

Megapoxy PM - Part B

Avoid contamination of drains, sewerage, creeks and waterways.
Product may be toxic to some aquatic organisms.

Section 13:	Disposal Consideration
--------------------	-------------------------------

Dispose all empty containers as per State & Council Regulation. Do not dispose near waterways, vegetation and tree roots. Empty containers and product should not be burned.

Section 14:	Transport Information
--------------------	------------------------------

UN. No.	Not Applicable
Shipping Name	Not Applicable
Class	Not classified as dangerous goods
Subsidiary Risk	Nil
Packaging Group	Not Applicable
Hazchem Code	Not Applicable
EPG	Not Applicable
Segregation	Not to be loaded with explosives, oxidising agents or organic peroxides.

For road, marine and air transport this product is not classified as dangerous goods within the context of National and International Transport Regulation.

Section 15:	Regulatory Information
--------------------	-------------------------------

The National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC : 10005 (1999)].

The National Standard for the Storage and Handling of Workplace Dangerous Goods [NOHSC : 1015 (2001)].

Section 16:	Other information
--------------------	--------------------------

Date of Preparation 01.07.02
Date of Revision 01.07.07
Reasons for Issue Five yearly update & new format
MSDS's are updated frequently. Please ensure you have the current copy.

This MSDS summarises at the date of issue our best knowledge of health and safety hazard information of the product, and in particular how to handle and use the product in the workplace. Since Vivacity Engineering Pty Ltd cannot anticipate or control the conditions under which the product may be used each user must, prior to usage, review this MSDS in the context to use

Megapoxy PM - Part B

and handling of the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact Vivacity Engineering Pty Ltd. Our responsibility for the product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.