



MATERIAL SAFETY DATA SHEET FOR: FULASEAL GREY

Replaces: NEW. Date of issue: 27/01/05

**1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

Product Name: Fulaseal Grey  
Other Names: Not applicable  
Recommended Use: Tilt up panel sealant

Company: H. B. Fuller  
Address: 16-22 Red Gum Drive, Dandenong South VIC 3175  
Telephone: (03) 9797 6222  
Emergency Telephone No: 1800 033 111

**2. HAZARD IDENTIFICATION**

*Not classified as hazardous according to criteria of Worksafe Australia*

**3. COMPOSITION**

Ingredients

CHEMICAL ENTITY	CAS NO	PROPORTION
Acrylic copolymer	Not available	Med
Limestone	1317-65-3	High
Water	7732-18-5	Med
Other ingredients determined not to be hazardous	Not applicable	Low

Low <10%	Med. 10-30%	High 30-60%	V High >60%
----------	-------------	-------------	-------------

**4. FIRST AID MEASURES**

**First Aid:**

Swallowed:

If swallowed, rinse mouth thoroughly with water. Give one glass of water or milk . Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Seek medical advice if any ill effects persist

Eyes:

If in eye, irrigate immediately with copious amounts of water for 15 minutes with eyelids held open. Seek medical advice if ill effects persist.

Skin:

Wash affected areas with copious quantities of water immediately.  
Remove contaminated clothing and wash before reuse. Seek medical advice if irritation persists.

Inhaled:

Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Keep comfortable, warm and at rest until fully recovered.

First Aid Facilities:

Have eyewashes available where contact with eyes can occur



MATERIAL SAFETY DATA SHEET FOR: FULASEAL GREY

Replaces: NEW. Date of issue: 27/01/05

**Advice To Doctor:**

Treat symptomatically.

**5. FIRE FIGHTING MEASURES**

Non flammable paste. In the dry state, burning may emit hazardous fumes. Fire fighters exposed to combustion products should wear self contained breathing apparatus. Extinguishing Media: Water spray, water fog, foam, carbon dioxide, dry chemical powder.

**6. ACCIDENTAL RELEASE MEASURES**

Contain - prevent contamination of waterways and drains. If the quantity spilled warrants it, immobilise it first using an absorbent and then transfer to a suitably labelled and sealable container for disposal. Dispose strictly in accordance with local industrial waste disposal and environmental protection regulation.

**7. HANDLING AND STORAGE**

Storage and Transport:

Keep containers securely sealed and protected against physical damage. Do not store below 5°C in direct sunlight

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Exposure Standards [NOHSC: 1004 (2004)]:

	<b>TWA</b>
Acrylamide	0.03 mg/m <sup>3</sup>
Butyl acrylate	55 mg/m <sup>3</sup>
Styrene monomer	213 mg/m <sup>3</sup>
Formaldehyde	1.2 mg/m <sup>3</sup>
Mineral turpentine	480mg/m <sup>3</sup>

Engineering Controls:

If not working in open air use good general ventilation that will ensure that atmospheric exposure standards are not exceeded. In confined spaces, use a local exhaust that will give sufficient face velocity away from the user to ensure that the exposure limits are not exceeded.

Personal Protection:

Avoid repeated and prolonged skin contact. Wear safety overalls, glasses and gloves. Always wash hands before smoking, eating, drinking or using the toilet.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: Thick, coloured paste

Melting Point: Not applicable

Boiling Point: Greater than 90°C

Vapour Pressure: Not available

Specific Gravity: 1.5

Flashpoint: Not applicable

Flammability Limits: Not applicable

Solubility in water: Miscible with water



MATERIAL SAFETY DATA SHEET FOR: FULASEAL GREY

Replaces: NEW. Date of issue: 27/01/05

**Other Properties:** None applicable

**10. STABILITY AND REACTIVITY**

Chemical Stability:

Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure

Hazardous Polymerisation:

None

Incompatibilities:

None

**11. TOXICOLOGICAL INFORMATION**

*ACUTE:*

Swallowed:

No adverse effects expected. Large amounts may cause nausea and vomiting or abdominal discomfort

Eye:

Direct contact with eye may result in irritation.

Skin:

Mild irritant.

Inhaled:

Not considered a normal route of exposure. May cause irritation to nose and throat if used in a poorly ventilated area.

*CHRONIC:*

Repeated or prolonged skin contact may lead to irritation

**12. ECOLOGICAL INFORMATION**

No information available

**13. DISPOSAL**

Dispose strictly in accordance with local industrial waste disposal and environmental protection regulation.

**14. TRANSPORT INFORMATION**

Manufacturer's Code: Not applicable

UN Number: Not assigned

Dangerous Goods Class: None assigned

Subsidiary Risk: None assigned

Hazchem Code: None assigned

Poisons Schedule: Not scheduled



**H.B. Fuller Company**



**MATERIAL SAFETY DATA SHEET FOR: FULASEAL GREY**

Replaces: NEW. Date of issue: 27/01/05

Packaging Group: None assigned

This product is not a Dangerous Good for the purpose of transport. No special transport precautions are required.

**15. REGULATORY INFORMATION**

Not applicable

**16. OTHER INFORMATION**

Technical Manager (03) 9797 6222

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular, how to safely handle and use the product in the workplace. Since H.B. Fuller Company Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for the products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.