

Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com
e-mail: sales@aitkenfreeman.com

Safety Data Sheet

1. Product Name: Anchorloc GG – Base Component

Classified as Hazardous

Identification

Company Name Aitken Freeman Pty Ltd

Address Unit 7, 7 – 9 Brough St. Springvale Vic 3171 **Contact:** Ph. (03) 9701 3955 Fx. (03) 9701 3956

2. Hazard Identification:

GHS Classification Skin corrosion/irritation - Category 2

Skin sensitisation - Sub-category 1B Acute aquatic toxicity - Category 2 Chronic aquatic toxicity - Category 2

Signal Word Hazard

Hazard Statement Causes skin irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

Pictogram(s) Exclamation mark, Environmental





Precautionary Statements

Prevention Read label before use.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash skin thoroughly after handling.

Contaminated work clothing should not be allowed out of the work place.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Response Collect spillage.


IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN:Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before re-use.

Disposal Dispose of contents/container to approved waste disposal plant



Aitken Freeman Pty Ltd Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com e-mail: sales@aitkenfreeman.com

3. Composition / information on ingredients

Ingredients	Name	CAS	Proportion
	Propane, 2,2-bis[p-(2,3- epoxypropoxy)phenyl]- polymers	25085-99-8	30 - 60%
	Diglycidyl ether of phenol -	28064-14-4	1 – 10%
	formaldhyde polymer		
	C12 – C14 glycidyl ether	68609-97-2	1 – 10%
	Ingredients determined to be non hazardous		Balance

4. First Aid Measures

Inhalation If inhaled, remove affected person from contaminated area. Keep at rest until

recovered. If symptoms persist seek medical attention.

Ingestion Do not induce vomiting. Wash out mouth thoroughly with water. Seek medical

attention.

Skin Wash affected area thoroughly with soap and water. Remove contaminated

clothing and wash before re-use or discard. Seek medical attention.

Eye contact If in eyes, hold eyelids apart and flush the eyes continuously with running water.

Continue flushing for several minutes until all contaminants are washed out

completely. Seek medical attention.

Advice to Doctor Treat symptomatically.

Other information For advice in an emergency, contact a Poisons Information Centre, 13 11 26, or a

doctor at once.

5. Fire fighting measures

Suitable Use carbon dioxide, dry chemical, foam or water mist.

Extinguishing media

Unsuitable DO NOT use water jets.

Extinguishing media


Hazards from Under fire conditions this product may emit toxic/irritating fumes including

Combustion Products carbon monoxide and carbon dioxide.

Specific Hazards arising from the ingredients

Combustible liquid. This product will readily burn under fire conditions.

Hazchem Code 3Z



Aitken Freeman Pty Ltd Factory 7, 7-9 Brough St, Springvale VIC 3171 PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com e-mail: sales@aitkenfreeman.com

Precautions in connection with fire Fire fighters should wear full protective clothing and self contained breathing apparatus operated in positive pressure mode. Water spray may be used to keep fire exposed containers cool.

6. Accidental Release Measures

Emergency Procedures Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Place inert absorbent, non-combustible material on to spillage. Use clean non sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal.

Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs, inform the local water and

waste management authorities in accordance with local regulations.

7. Handling and storage

Precautions for safe Handling

Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Avoid inhalation of vapours and mists, and skin or eye contact. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards or personal hygiene, ie. Washing hands prior to eating, drinking, smoking or using toilet facilities.

Conditions for safe storage, including any Incompatibilities

Store in a cool, dry, well ventilated area away from heat, sources of ignition, oxidising agents, food stuffs, and clothing, and out of direct sunlight.

Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Co not pressurise, cut, heat, or weld containers as they may contain hazardous residues. For information on the design of the store room, reference should be made to Australian Standard AS1940 - The storage of flammable and combustible liquids. Reference should also be made to all state and federal regulations.

8. Exposure Controls

Occupational exposure limit values No exposure standards have been established for this material by Safework Australia. However as with all chemicals, exposure should be kept to the lowest

possible levels.

Appropriate

engineering controls


Biological limit values No biological limit allocated

Use with good ventilation. If mists or vapours are produced, local exhaust

ventilation should be used.

Respiratory protection

If engineering controls are not effective in controlling airbourne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian standards AS 1715, Selection, Use, and Maintenance of Respiratov Protective Devices, in order to make any necessary changes for individual circumstances.



Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com e-mail: sales@aitkenfreeman.com

Eye Protection Safety glasses with side shields or chemical goggles should be worn. Final choice

of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australiann Standard AS 1337 – Eye

Protectors for Industrial Applications.

Hand Protection Wear gloves of impervious material. Final choice of appropriate gloves will vary

with individual circumstances ie methods of handling or according to risk

assessments undertaken. Reference should be made to AS2161.1 Occupational

protective gloves - Selection, Use, and Maintenance.

Body Protection Suitable protective work wear, EG Cotton overalls buttoned at the neck and wrist is

recommended. Chemical resistant apron is recommended where large quantities

are handled.

9. Physical and Chemical Properties

Form: Off white, soft paste Solubility: Not miscible with water

Specific Gravity (20°C): 1.3 – 1.5 Relative Vapour Density (air=1): >1

Vapour Pressure (kPa @ 20°C):

Flash Point (°C):

Flammability Limits (%):

Not Available

> 150°C

Not Applicable

Autoignition Temperature (°C): 400°C

% Volatile by Volume:

Melting Point/Range (°C):

Boiling Point/Range (°C):

PH:

Not Applicable

Not Available

Not Available

Not Available

Not Available

Not Available

Viscosity: Not Applicable

10 Stability and Reactivity

Chemical Stability Unstable in the presence of incompatible materials See below

Possibility of Hazardous Reactions may polymerise in contact with heat, organic and inorganic free radical producing

initiators

may polymerise with evolution of heat in contact with oxidisers, strong acids, bases

and amines

may react violently with strong oxidisers, permanganates, peroxides, acyl halides,


alkalis, ammonium persulfate, bromine dioxide

may attack some forms of plastics, coatings, and rubber

Avoid reaction with oxidising agents

Conditions to Avoid Contact with any of the above

Hazardous Decomposition Products Carbon monoxide



Aitken Freeman Pty Ltd Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com e-mail: sales@aitkenfreeman.com

11 Toxicological Information

Inhaled The material can cause respiratory irritation in some persons. The body's response to

such irritation can cause further lung damage.

Not normally a hazard due to non-volatile nature of product

Ingestion High molecular weight material; on single acute exposure would be expected to pass

through gastrointestinal tract with little change / absorption.

Skin ContactThe material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact

dermatitis which is characterised by redness, swelling and blistering. Open cuts, abraded or irritated skin should not be exposed to this material

Eye May prod
Chronic Long-term

May produce eye irritation in some persons and produce eye damage

Long-term exposure to respiratory irritants may result in disease of the airways

involving difficult breathing and related systemic problems.

Skin contact with the material is more likely to cause a sensitisation reaction in some

persons compared to the general population.

Toxic: danger of serious damage to health by prolonged exposure through inhalation.

Not available

12 Ecological Information

Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Significant environmental findings are limited. Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit common characteristics with respect to environmental fate and ecotoxicology.

13 Disposal Considerations

Product / Packaging Disposal

Containers may still present a chemical hazard/ danger when empty.

Legislation addressing waste disposal requirements may differ by state and/ or territory. Each user must refer to laws operating in their area.

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

DO NOT allow wash water from cleaning or process equipment to enter drains.

It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these


should be considered first. Where in doubt contact the responsible authority.

Recycle wherever possible or consult manufacturer for recycling options.

Consult State Land Waste Authority for disposal.

Bury or incinerate residue at an approved site.

Recycle containers if possible, or dispose of in an authorised landfill.



Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com
e-mail: sales@aitkenfreeman.com

14 Transport Information

Labels Required





Land Transport UN No. 3082

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains bisphenol A/

epichlorohydrin resin)

Transport Hazard Class Class 9
Packing Group

Environmental Hazard Not Applicable

Hazchem 3Z

15 Regulatory Information

Safety, health and environmental regulations / legislation specific for the substance or mixture BISPHENOL A/ DIGLYCIDYL ETHER POLYMER, HIGH MOLECULAR WEIGHT(25068-38-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Substances Information System - Consolidated Lists Australia Inventory of Chemical Substances (AICS)

National InventoryStatusAustralia - AICSYCanada - DSLY

Canada - NDSL N (bisphenol A/ diglycidyl ether polymer, high molecular weight)

China - IECSC
Europe - EINEC / ELINCS /NLP

Japan - ENCS N (bisphenol A/ diglycidyl ether polymer, high molecular weight)

 Korea - KECI
 Y

 New Zealand - NZIoC
 Y

 Philippines - PICCS
 Y

 USA - TSCA
 Y


Legend:

Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt

16 Other Information

Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

Revision date 1st October 2020



Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com e-mail: sales@aitkenfreeman.com

Safety Data Sheet

1. Product Name: Anchorloc GG - Hardener Component

Classified as Hazardous

Identification

Company Name Aitken Freeman Pty Ltd

Unit 7, 7 – 9 Brough St. Springvale Vic 3171 **Address** Fx. (03) 9701 3956 **Contact:** Ph. (03) 9701 3955

2. Hazard Identification:

GHS Classification

Acute Tox. 4 (oral) Acute toxicity Acute Tox. 4 (dermal) Acute toxicity

Skin Corr./Irrit. Skin corrosion/irritation 1B Serious eye damage/eye Eye Dam./Irrit.

irritation

Skin Sens. 1A Skin sensitization

Hazardous to the aquatic Aquatic Acute 3

environment - acute Hazardous to the aquatic

Aquatic Chronic 3 environment - chronic

Signal Word Danger

Hazard Statement

Harmful in contact with skin.

Harmful if swallowed.

May cause an allergic skin reaction.

Causes severe skin burns and eye damage.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

Wear protective gloves/clothing/eye protection/face protection P280

Do not breathe dust or mist. P260

P273 Avoid release to the environment.

Contaminated work clothing should not be allowed out of the workplace. P272

P270 Do not eat, drink or smoke when using this product.

P264 Wash with plenty of water and soap thoroughly after handling

Precautionary Statements (Response):

Immediately call a POISON CENTER or doctor/physician. P310

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.


Rinse skin with water/shower

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P361 + P364 Take off immediately all contaminated clothing and wash it before reuse.

Precautionary Statements (Storage): P405 Store locked up.



Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com
e-mail: sales@aitkenfreeman.com

Pictogram(s)





3. Composition / information on ingredients

Ingredients Name	CAS	Proportion
Polyether amine	2855-13-2	30 – 60 %
Triethylene tetramine	112-24-3	1 – 10 %
Ingredients determined to be non hazardous		Balance

4. First Aid Measures

Inhalation If inhaled, remove affected person from contaminated area. Keep at rest until

recovered. If symptoms persist seek medical attention.

Ingestion Do not induce vomiting. Wash out mouth thoroughly with water. Seek medical

attention.

Skin Wash affected area thoroughly with soap and water. Remove contaminated

clothing and wash before re-use or discard. Seek medical attention.

Eye contact If in eyes, hold eyelids apart and flush the eyes continuously with running water.

Continue flushing for several minutes until all contaminants are washed out

completely. Seek medical attention.

First Aid Facilities

Eye wash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other information

For advice in an emergency, contact a Poisons Information Centre, 13 11 26, or a

doctor at once.

5. Fire fighting measures

Suitable Extinguishing media

Use carbon dioxide, dry chemical, alcohol resistant foam, or water mist.

Unsuitable

Extinguishing media

DO NOT use water jets.

•


Hazards from

Under fire conditions this product may emit toxic/irritating fumes including

Combustion Products carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific Hazards arising from the ingredients

Combustible liquid. This product will readily burn under fire conditions.



Aitken Freeman Pty Ltd Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com e-mail: sales@aitkenfreeman.com

Hazchem Code

•3Z

Precautions in connection with fire Fire fighters should wear full protective clothing and self contained breathing apparatus operated in positive pressure mode. Water spray may be used to keep fire exposed containers cool.

6. Accidental Release Measures

Emergency Procedures Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Place inert absorbent, non-combustible material on to spillage. Use clean non sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal.

Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs, inform the local water and waste management authorities in accordance with local regulations.

7. Handling and storage

Precautions for safe Handling

Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Avoid inhalation of vapours and mists, and skin or eye contact. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards or personal hygiene. ie. Washing hands prior to eating, drinking, smoking or using toilet facilities.

Conditions for safe storage, including any Incompatibilities

Store in a cool, dry, well ventilated area away from heat, sources of ignition, oxidising agents, food stuffs, and clothing, and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Co not pressurise, cut, heat, or weld containers as they may contain hazardous residues. For information on the design of the store room, reference should be

made to Australian Standard AS1940 – The storage of flammable and combustible

liquids. Reference should also be made to all state and federal regulations.

8. Exposure Controls

Occupational exposure limit values No exposure standards have been established for this material by Safework Australia. However as with all chemicals, exposure should be kept to the lowest

possible levels.

Biological limit values

Appropriate engineering controls No biological limit allocated

Use with good ventilation. If mists or vapours are produced, local exhaust


ventilation should be used.

Respiratory protection

If engineering controls are not effective in controlling airbourne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian standards AS 1715, Selection, Use, and Maintenance of Respiratoy Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australiann Standard AS 1337 - Eye Protectors for Industrial Applications.



Aitken Freeman Pty Ltd Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com e-mail: sales@aitkenfreeman.com

Hand Protection Wear gloves of impervious material. Final choice of appropriate gloves will vary

with individual circumstances ie methods of handling or according to risk

assessments undertaken. Reference should be made to AS2161.1 Occupational

protective gloves - Selection, Use, and Maintenance.

Body Protection Suitable protective work wear, EG Cotton overalls buttoned at the neck and wrist is

recommended. Chemical resistant apron is recommended where large quantities

are handled.

9. Physical and Chemical Properties

Form: Soft black paste

Solubility: Not miscible with water

Specific Gravity (20°C): 0.96 – 0.98
Relative Vapour Density (air=1): Not Available
Vapour Pressure (kPa @ 20°C): Not Available
Flash Point (°C): > 96°C

Flammability Limits (%):

Autoignition Temperature (°C):

% Volatile by Volume:

Melting Point/Range (°C):

Boiling Point/Range (°C):

PH:

Not Applicable

Not Applicable

Not Available

Not Available

Not Available

Not Available

Not Available

Viscosity: Not Applicable

10 Stability and Reactivity

Possibility of hazardous reactions

The product is chemically stable.

Exothermic reaction. Reacts with acids.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. See MSDS section 7 - Handling and storage.

Incompatible materials

Strong oxidizing agents, acids, halogenated compounds.

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide, nitrogen oxides

11 Toxicological Information

InhaledThe material can cause respiratory irritation in some persons. The body's response to

such irritation can cause further lung damage.

Not normally a hazard due to non-volatile nature of product

Ingestion High molecular weight material; on single acute exposure would be expected to pass


through gastrointestinal tract with little change / absorption.

Skin Contact The material may cause moderate inflammation of the skin either following direct

contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

Open cuts, abraded or irritated skin should not be exposed to this material

Eye May produce eye irritation in some persons and produce eye damage



Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com
e-mail: sales@aitkenfreeman.com

Chronic

Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

Toxic: danger of serious damage to health by prolonged exposure through inhalation.

Not available

Toxicity

12 Ecological Information

Persistence and degradability No further relevant information available.

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Ecotoxical effects: Not determined

Remark: Toxic for fish

13 Disposal Considerations

Product / Packaging Disposal

Containers may still present a chemical hazard/ danger when empty.

Legislation addressing waste disposal requirements may differ by state and/ or territory. Each user must refer to laws operating in their area.

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

DO NOT allow wash water from cleaning or process equipment to enter drains.

It may be necessary to collect all wash water for treatment before disposal.

In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.

Where in doubt contact the responsible authority.

Recycle wherever possible or consult manufacturer for recycling options.

Consult State Land Waste Authority for disposal. Bury or incinerate residue at an approved site.

Recycle containers if possible, or dispose of in an authorised landfill.

14 Transport Information

Labels Required





Land Transport UN No. 2735

Proper Shipping Name Transport Hazard Class Packing Group

Environmental Hazard


Hazchem

2735 AMINES, LIQUID, CORROSIVE, N.O.S. (Coco amines)

Class 8

Not Applicable

·3Z



Aitken Freeman Pty Ltd Factory 7, 7-9 Brough St, Springvale VIC 3171

PO Box 548, Noble Park VIC 3174

Phone: (03) 9701 3955 Fax: (03) 9701 3956

Internet: www.aitkenfreeman.com
e-mail: sales@aitkenfreeman.com

15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms

GHS05 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:
- · Hazard statements

Harmful if swallowed.

Harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

· Precautionary statements

Do not breathe dusts or mists.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E1 Hazardous to the Aquatic Environment

16 Other Information

Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.