

Revision date 19-Dec-2022

BOSTIK 1831 ADHESIVE BLUE

Revision Number 1.01 Supersedes Date: 24-Oct-2021

\_\_\_

### Section 1: Identification: Product identifier and chemical identity

**Product identifier** 

Product Name BOSTIK 1831 ADHESIVE BLUE

**Product Code(s)** 

30608605

30608520; 30608605; 30803244

Other means of identification

Proper Shipping Name Adhesives

UN number or ID number UN1133

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Adhesive

Uses advised against No information available

Details of manufacturer or importer

<u>Supplier</u>

Bostik Australia Pty Ltd 51-71 High Street, Thomastown Victoria Australia

Tel: 613 9279-9333

Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

### Section 2: Hazard(s) identification

## GHS Classification

Flammable liquids	Category 2 - (H225)
Aspiration hazard	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Specific target organ toxicity (single exposure)	Category 3 - (H336)

### Label elements

Flame Exclamation mark Health hazard

Australia - EN Page 1 / 12

**BOSTIK 1831 ADHESIVE BLUE Revision Number** 1.01

·

Revision date 19-Dec-2022

Supersedes Date: 24-Oct-2021



#### Signal word DANGER

#### **Hazard statements**

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Ground and bond container and receiving equipment

Use non-sparking tools

Take action to prevent static discharges

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container closed

Wear protective gloves/clothing and eye/face protection

Keep cool

IF ON SKIN: Wash with plenty of water and soap

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a doctor if you feel unwell

IF SWALLOWED: Immediately call a doctor

Do NOT induce vomiting

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### **Precautionary Statements - Storage**

Store in well-ventilated place

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Other hazards which do not result in classification

In use, may form flammable/explosive vapor-air mixture.

### Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

## Poison Schedule Number

## Label requirements in accordance with SUSMP

**CAUTION** 

KEEP OUT OF REACH OF CHILDREN

READ SAFETY DIRECTIONS BEFORE OPENING OR USING

## Section 3: Composition and information on ingredients, in accordance with Schedule 8

#### Substance

Not applicable

Australia - EN Page 2/12

**BOSTIK 1831 ADHESIVE BLUE** 

Revision Number 1.01 Supersedes Date: 24-Oct-2021

\_\_\_

#### Mixture

Chemical name	CAS No	Weight-%
Naphtha, petroleum, hydrotreated light, <0.1% Benzene	64742-49-0	30 - 60
Cyclohexane	110-82-7	0 - <10
Pentane	109-66-0	0 - <10
Methylcyclopentane	96-37-7	0 - <10
Hexane	110-54-3	0 - <10
Non-hazardous ingredients	Proprietary	Balance

#### Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26

Poisons Information Center, New Zealand: 0800 764 766

**Description of first aid measures** 

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

**Inhalation** Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing

has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention.

Revision date 19-Dec-2022

Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Do not rub affected area.

**Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Get medical attention if irritation develops and persists.

**Ingestion** Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Get immediate medical attention.

**Self-protection of the first aider** Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth

resuscitation. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapor

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed

unless the risk is justified by the presence of additional toxic substances.

## Section 5: Firefighting measures

#### **Suitable Extinguishing Media**

Australia - EN Page 3/12

**BOSTIK 1831 ADHESIVE BLUE** 

**Revision Number** 1.01 Supersedes Date: 24-Oct-2021

Suitable extinguishing media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

No information available. Unsuitable extinguishing media

Specific hazards arising from the chemical

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Revision date 19-Dec-2022

Carbon oxides. Hydrocarbons. **Hazardous combustion products** 

Special protective actions for fire-fighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

#### Section 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See Personal precautions

> section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

**Environmental precautions** 

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or **Environmental precautions** 

spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Stop leak if you can do it without risk. Do not touch or walk through spilled material. A Methods for containment

vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand

or other non-combustible material and transfer to containers for later disposal.

Take precautionary measures against static discharges. Dam up. Soak up with inert Methods for cleaning up

absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### Section 7: Handling and storage, including how the chemical may be safely used

#### Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from

> heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to

Australia - EN Page 4/12

**BOSTIK 1831 ADHESIVE BLUE** 

Revision Number 1.01 Supersedes Date: 24-Oct-2021

\_\_\_

package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of

Revision date 19-Dec-2022

insufficient ventilation, wear suitable respiratory equipment.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should

not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the

product. Wear suitable gloves and eye/face protection.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked

up. Keep out of the reach of children. Store away from other materials.

Recommended storage

temperature

Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

**Incompatible materials** Strong acids. Strong bases. Strong oxidizing agents.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

## Section 8: Exposure controls and personal protection

#### **Control parameters**

#### **Exposure Limits**

Chemical name	Australia
Cyclohexane	TWA: 100 ppm
110-82-7	TWA: 350 mg/m <sup>3</sup>
	STEL: 300 ppm
	STEL: 1050 mg/m <sup>3</sup>
Pentane	TWA: 600 ppm
109-66-0	TWA: 1770 mg/m <sup>3</sup>
	STEL: 750 ppm
	STEL: 2210 mg/m <sup>3</sup>
Hexane	TWA: 20 ppm
110-54-3	TWA: 72 mg/m <sup>3</sup>

#### **Biological occupational exposure limits**

## **Appropriate engineering controls**

**Engineering controls** Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

**Skin and body protection** Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

**Hand protection** Wear suitable gloves. Impervious gloves.

**Respiratory protection** Organic gases and vapors filter conforming to EN 14387.

Australia - EN Page 5/12

**BOSTIK 1831 ADHESIVE BLUE** 

**Revision Number** 1.01 Supersedes Date: 24-Oct-2021

Revision date 19-Dec-2022

**Environmental exposure controls** No information available.

## Section 9: Physical and chemical properties

#### Information on basic physical and chemical properties

Physical state Liquid **Appearance** Liquid Color Blue Odor Solvent

**Odor threshold** No information available

**Property Values** Remarks • Method

No data available Not applicable Insoluble in water pН

pH (as aqueous solution) No data available Melting point / freezing point No data available

51 - 61 °C Initial boiling point and boiling (Isohexane)

range

-7 °C Flash point CC (closed cup) (based on components)

(Isohexane) **Evaporation rate** No data available

Not applicable for liquids .

**Flammability** 

Flammability Limit in Air

Upper flammability or explosive 7.4 limits

Lower flammability or explosive 1.1

limits

Vapor pressure No data available No data available Relative vapor density

0.75 Relative density Water solubility Insoluble in water

Solubility(ies) No data available **Partition coefficient** No data available **Autoignition temperature** > 200 °C **Decomposition temperature** No data available Kinematic viscosity No data available **Dynamic viscosity** 600 - 800 mPas

**Explosive properties** No information available **Oxidizing properties** No information available

Other information

Solid content (%) No information available No information available Density

523 g/L SCAQMD Method 304-91 **VOC** content

## Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

**Stability** Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical None.

impact

Sensitivity to static discharge Yes.

Australia - EN Page 6/12

**BOSTIK 1831 ADHESIVE BLUE** 

Revision Number 1.01 Supersedes Date: 24-Oct-2021

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

**Incompatible materials** 

**Incompatible materials** Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition

products

None known based on information supplied.

## Section 11: Toxicological information

#### **Acute toxicity**

## Information on likely routes of exposure

#### **Product Information**

**Inhalation** Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Revision date 19-Dec-2022

**Eye contact** Specific test data for the substance or mixture is not available. May cause irritation.

**Skin contact** Repeated exposure may cause skin dryness or cracking. Specific test data for the

substance or mixture is not available. Causes skin irritation. (based on components).

**Ingestion** Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may

cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause

redness and tearing of the eyes. Inhalation of high vapor concentrations may cause

symptoms like headache, dizziness, tiredness, nausea and vomiting.

## Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg

ATEmix (inhalation-vapor) 3,569.70 mg/l

## **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Naphtha, petroleum, hydrotreated light, <0.1% Benzene	>5000 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	=73680 ppm (Rattus) 4 h
Cyclohexane	=12705 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	>9500 ppm (Rattus) 4 h
Pentane	>2000 mg/kg (Rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=364 g/m³ (Rattus) 4 h
Hexane	=25 g/kg (Rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=48000 ppm (Rattus) 4 h

Australia - EN Page 7 / 12

**BOSTIK 1831 ADHESIVE BLUE** 

Revision Number 1.01 Supersedes Date: 24-Oct-2021

Revision date 19-Dec-2022

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**Classification based on data available for ingredients. Causes skin irritation.

Component Information					
Hexane (110-54-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal		24 hours	irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

#### Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
Naphtha, petroleum, hydrotreated	Carc. 1A		
light, <0.1% Benzene			
64742-49-0			

Legend

IARC (International Agency for Research on Cancer) Group 3 - Not Classifiable as to Carcinogenicity in Humans

**Reproductive toxicity** No information available.

**STOT - single exposure** May cause drowsiness or dizziness. May cause respiratory irritation.

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

**Aspiration hazard** May be fatal if swallowed and enters airways.

### Section 12: Ecological information

## **Ecotoxicity**

## **Aquatic ecotoxicity**

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Naphtha, petroleum,	-	LC50: =8.41mg/L (96h,	-	LC50: =2.6mg/L (96h,
hydrotreated light, <0.1%		Oncorhynchus mykiss)		Chaetogammarus
Benzene				marinus)
64742-49-0				
Cyclohexane	EC50 72 h > 9.3 mg/L	LC50: 23.03 - 42.07mg/L	EC50 = 85.5  mg/L  5  min	EC50: >0.9 mg/L (24h,
110-82-7	(Pseudokirchnerella	(96h, Pimephales	EC50 = 93 mg/L 10 min	Daphnia magna)

Australia - EN Page 8 / 12

**BOSTIK 1831 ADHESIVE BLUE** 

**Revision Number** 1.01 Supersedes Date: 24-Oct-2021

Revision date 19-Dec-2022

	subcapitata)	promelas) LC50: 48.87 - 68.76mg/L (96h, Poecilia reticulata) LC50: 3.96 - 5.18mg/L (96h, Pimephales promelas)		
		LC50: 24.99 - 44.69mg/L (96h, Lepomis macrochirus)		
Pentane 109-66-0	-	LC50: =11.59mg/L (96h, Pimephales promelas) LC50: =9.87mg/L (96h, Oncorhynchus mykiss) LC50: =9.99mg/L (96h, Lepomis macrochirus)	-	EC50: =9.74mg/L (48h, Daphnia magna)
Hexane 110-54-3	-	LC50: 2.1 - 2.98mg/L (96h, Pimephales promelas)	-	EC50: >1000mg/L (24h, Daphnia magna)

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

There is no data for this product. **Bioaccumulation** 

**Component Information** 

Chemical name	Partition coefficient
Cyclohexane 110-82-7	3.93
Pentane 109-66-0	3.45
Hexane 110-54-3	4

**Mobility** 

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

## Section 13: Disposal considerations

**Disposal methods** 

Waste from residues/unused Should not be released into the environment. Dispose of in accordance with local products

regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

## Section 14: Transport information

**UN** number or ID number UN1133

Australia - EN Page 9/12

**BOSTIK 1831 ADHESIVE BLUE** 

Revision Number 1.01 Supersedes Date: 24-Oct-2021

Revision date 19-Dec-2022

UN proper shipping name Adhesives

Transport hazard class(es) 3
Packing group II
Limited quantity (LQ) 5 L

**Description** UN1133, Adhesives, 3, II

Hazchem code •3YE

IATA

UN number or ID number
Transport hazard class(es)
Packing group
II
ERG Code
Special Provisions
Limited quantity (LQ)
UN1133
3
Limited provisions
UN1133
A
Limited provisions
UN1133

**Description** UN1133, Adhesives, 3, II

**IMDG** 

UN number or ID number
Transport hazard class(es)
Packing group
II
EmS-No
F-E, S-D
Limited Quantity (LQ)
Marine pollutant
UN1133
F-E, S-D
II
NP

**Description** UN1133, Adhesives, 3, II, (-7°C c.c.)

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

### Section 15: Regulatory information

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **National regulations**

## <u>Australia</u>

See section 8 for national exposure control parameters

## Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 5

## Major hazard (accident/incident planning) regulation

Verify that license requirements are met

<u>Hazardous chemical</u> Liquids that meet the criteria for Class 3 Packing Group II or III

Liquids that meet the criteria for Class 3 Packing Group II or III Liquids with flash points <61°C kept above their boiling points

at ambient conditions

## National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory	
Cyclohexane	10 tonne/yr Threshold category 1	
110-82-7	20 MW Threshold category 2b total	
	60000 MWH Threshold category 2b total	
	1 tonne/h Threshold category 2a total	
	25 tonne/yr Threshold category 1a total	

Threshold quantity (T)

50 000

200

Australia - EN Page 10 / 12

**BOSTIK 1831 ADHESIVE BLUE** 

Revision Number 1.01 Supersedes Date: 24-Oct-2021

Revision date 19-Dec-2022

\_\_\_

	400 toppo/yr Throshold category 2a total		
	400 tonne/yr Threshold category 2a total		
	2000 tonne/yr Threshold category 2b total		
Pentane	20 MW Threshold category 2b total		
109-66-0	60000 MWH Threshold category 2b total		
	1 tonne/h Threshold category 2a total		
	25 tonne/yr Threshold category 1a total		
	400 tonne/yr Threshold category 2a total		
	2000 tonne/yr Threshold category 2b total		
Methylcyclopentane	20 MW Threshold category 2b total		
96-37-7	60000 MWH Threshold category 2b total		
	1 tonne/h Threshold category 2a total		
	25 tonne/yr Threshold category 1a total		
	400 tonne/yr Threshold category 2a total		
	2000 tonne/yr Threshold category 2b total		
Hexane	10 tonne/yr Threshold category 1		
110-54-3	20 MW Threshold category 2b total		
	60000 MWH Threshold category 2b total		
	1 tonne/h Threshold category 2a total		
	25 tonne/yr Threshold category 1a total		
	400 tonne/yr Threshold category 2a total		
	2000 tonne/yr Threshold category 2b total		

#### **International Inventories**

AIIC Listed
NZIOC Not Listed
ENCS Not Listed
IECSC Not Listed
KECL Not Listed
PICCS Not Listed

#### Legend:

AIIC - Australian Inventory of Industrial Chemicals

**NZIoC** - New Zealand Inventory of Chemicals

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

#### **International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

## **Europe**

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorization:**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### 2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Australia - EN Page 11 / 12

**BOSTIK 1831 ADHESIVE BLUE** 

Revision Number 1.01 Supersedes Date: 24-Oct-2021

Revision date 19-Dec-2022

### Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 19-Dec-2022

**Revision Note** 

\*\*\*Indicates updated data since last publication.

#### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value \* Skin designation

C Carcinogen

**Section 11: TOXICOLOGICAL INFORMATION** 

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet** 

Australia - EN Page 12/12