

FLOWFILL GROUT GP Revision Number 1.01 Revision date 10-Mar-2021 Supersedes Date: 03-May-2018

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name FLOWFILL GROUT GP

Product Code(s) 30840122

30840122; 30840411

Other means of identification

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Grout

Uses advised against No information available

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd 51-71 High Street, Thomastown Victoria Australia

Tel: 613 9279-9333

Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Based on available information, this material is classified as hazardous according to criteria of Safe Work Australia

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)

Label elements

Exclamation mark Health hazard Corrosion

Australia - EN Page 1/9

FLOWFILL GROUT GP Revision Number 1.01

Supersedes Date: 03-May-2018

Revision date 10-Mar-2021



Signal word

Danger

Hazard statements

H315 - Causes skin irritation

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention

P264 - Wash face, hands and any exposed skin thoroughly after handling

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P271 - Use only outdoors or in a well-ventilated area

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

P321 - Specific treatment (see supplementary first aid information on this label)

P314 - Get medical advice/attention if you feel unwell

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P362 - Take off contaminated clothing and wash before reuse

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

Precautionary Statements - Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

Precautionary Statements - Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
Quartz	14808-60-7	30 - 60%
Cement, portland, chemicals (Chromium VI reduced)	65997-15-1	30 - 60%
Non-hazardous ingredients	Proprietary	Balance

Australia - EN Page 2/9

FLOWFILL GROUT GP Revision date 10-Mar-2021 **Revision Number** 1.01 Supersedes Date: 03-May-2018

Section 4: First aid measures

Poisons Information Center, Australia: 13 11 26 **Emergency telephone number**

Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed

or concerned: Get medical advice/attention.

Eye contact Do not rub affected area. Immediately flush with plenty of water. After initial flushing,

remove any contact lenses and continue flushing for at least 15 minutes. Consult an

ophthalmologist.

Skin contact Brush off loose particles from skin. Remove material from skin immediately. Take off

contaminated clothing and wash before reuse.

Clean mouth with water and drink afterwards plenty of water. Never give anything by Ingestion

mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section Self-protection of the first aider

8).

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Causes serious eye damage. Irritating to skin. Inhalation of dust in

high concentration may cause irritation of respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g.

when kneeling in wet cement even when wearing trousers.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Note to physicians

Section 5: Firefighting measures

Suitable extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the No information available.

chemical

fire-fighters

Special protective actions for fire-fighters

Special protective equipment for

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Australia - EN Page 3/9

FLOWFILL GROUT GP

Revision Number 1.01

Revision Number 1.01

Revision Number 03-May-2018

Personal precautions Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal

protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

Methods and material for containment and cleaning up

Methods for containmentCover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry.

Prevent dust cloud.

Methods for cleaning up Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect

dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep

up spilled material and place in suitable container. Avoid generating dust.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Avoid generation of dust. Avoid contact with skin, eyes or

clothing. Use personal protection equipment. Take off contaminated clothing and wash

before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children. Keep the packing dry and well sealed to prevent

contamination and absorption of humidity.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical name	Australia
Quartz	0.05 mg/m³ TWA
14808-60-7	
Cement, portland, chemicals (Chromium VI reduced) 65997-15-1	10 mg/m³ TWA

OEL as published by Safe Work Australia

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Australia - EN Page 4/9

FLOWFILL GROUT GP
Revision Number 1.01

Revision Number 1.01

Revision Number 03-May-2018

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing.

Hand protection Wear suitable gloves. Impervious gloves.

exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical stateSolidAppearancePowderColorGrayOdorOdorless

Odor threshold No information available

Property Values Remarks • Method

pH No data available
Melting point / freezing point No data available
Initial boiling point and boiling
No data available

range

Flash point

Evaporation rate
Flammability

No data available
No data available
No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressureNo data availableRelative vapor densityNo data available

Relative density 1.6

Water solubility Insoluble in water Cement based products react and solidify in contact

with water

Solubility(ies) No data available **Partition coefficient** No data available No data available **Autoignition temperature Decomposition temperature** No data available Kinematic viscosity No data available No data available Dynamic viscosity **Explosive properties** No information available **Oxidizing properties** No information available

Other information

Solid content (%)

VOC Content (%)

Liquid Density

No information available
No information available

Section 10: Stability and reactivity

Reactivity

Reactivity Product cures with moisture.

Australia - EN Page 5/9

FLOWFILL GROUT GP Revision date 10-Mar-2021 **Revision Number** 1.01 Supersedes Date: 03-May-2018

Chemical stability

Stability Stable under recommended storage conditions. Keep away from Incompatible materials.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge

None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Product cures with moisture.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum. Incompatible materials

Hazardous decomposition products

Hazardous decomposition

products

Carbon oxides.

Section 11: Toxicological information

Acute Toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Severely irritating to eyes.

Causes serious eye damage. May cause burns. May cause irreversible damage to eyes.

(based on components).

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation.

(based on components).

Specific test data for the substance or mixture is not available. Ingestion may cause Ingestion

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Redness. Burning. May cause blindness. May cause redness and tearing of the eyes.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

19,197.00 mg/kg ATEmix (oral)

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	>2000 mg/kg (Rattus)	-	-
Cement, portland, chemicals (Chromium VI reduced)	-	>2000 Kg/mg (Lapin)	>5 g/m³ (Rattus)

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Australia - EN Page 6/9

FLOWFILL GROUT GP Revision Number 1.01

vision Number 1.01 Supersedes Date: 03-May-2018

Revision date 10-Mar-2021

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious

eye damage.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a

carcinogen.

Chemical name	SafeWork Australia	European Union	IARC
Quartz	Carc. 1A		Group 1
14808-60-7			•

Reproductive toxicity No information available.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure if inhaled.

Aspiration hazard Not applicable.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity .

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Mobility

Mobility in soil No information available.

Mobility No information available.

Other Adverse Effects

Other adverse effects No information available.

Section 13: Disposal considerations

Waste treatment methods

Australia - EN Page 7/9

FLOWFILL GROUT GP

Revision Number 1.01

Revision Number 1.01

Revision date 10-Mar-2021

Supersedes Date: 03-May-2018

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

Section 14: Transport information

ADG Not regulated

IMDG Not regulated

Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

National pollutant inventory

Subject to reporting requirement

International Inventories

AICS
NZIOC
Listed
ENCS
Not Listed
IECSC
Not Listed
KECL
PICCS
Not Listed
Not Listed
Not Listed

Legend:

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Australia - EN Page 8/9

FLOWFILL GROUT GP

Revision Number 1.01

Revision Number 1.01

Revision Number 2.018

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2011/65/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 10-Mar-2021

Revision note

SDS sections updated. 9. 11.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

C Carcinogen

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

<u>Disclaime</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

Australia - EN Page 9/9