



# GAP SEAL

## GENERAL PURPOSE, ACRYLIC FLEXIBLE FILLER

15 February 2017

### YOUR SMART ADVANTAGES

- Excellent sealing and adhesion
- Slump resistant
- Skins within 15 minutes
- Can be over painted after 2 hours\*
- Water clean up
- Environmentally friendly
- Low VOC

### USES

Bostik Gap Seal is a general purpose, water based, acrylic gap filler, suitable for use on interior and exterior areas prior to painting. It offers excellent adhesion properties suitable for sealing gaps and low movement joints.

Bostik Gap Seal can be used on:

- Skirting boards, architraves, plasterboard, window and door frames
- For low movement joints, between light partition walls
- Filling cracks in plaster, brickwork, concrete aluminum, wood and glass

### PRODUCT CHARACTERISTICS

Colour	White
Viscosity	Smooth paste like consistency
Composition	Water based acrylic
Coverage	10mm bead: 10m per cartridge
Application temperature	5 to 35°C
Product codes	
450g cartridge/20 per carton	30605381

### TYPICAL PERFORMANCE DATA (approx.)

Service temperature	-5 to 75°C
Skin time	5 minutes
Full cure	2-3 days depending on temperature
Specific gravity	1.6

Total joint movement	± 5%
Maximum joint width	Up to 25mm in localized areas

### DIRECTIONS FOR USE

Read and understand the Safety Data Sheet before using this product. SDS can be acquired by visiting [www.bostik.com.au](http://www.bostik.com.au) or by scanning the relevant QR code on pack.

### SURFACE PREPARATION

1. Ensure all surfaces are clean, dry and free from dust and grease
2. Remove all loose materials (including old filler) from working area

### APPLICATION

1. Hold caulking gun at a 45° angle and squeeze trigger at even pressure
2. While the caulk is being dispensed, move the caulking gun along the crack or gap at an even speed
3. Smooth off with wet finger or scrape off lightly with a wet putty knife or damp cloth
4. Becomes touch dry within 30 minutes under normal conditions

### \*PAINTABILITY

Bostik Gap Seal can be painted over with most types of paint. Depending on the gap size and weather conditions; it can be painted over after 2 hours for acrylic paint and about 2-3 days for oil based paint. In general, the larger the gap sizes, the longer the drying time.

### LIMITATIONS

Do not use to provide a seal where joint movement is more than 10%. Not recommended for:

- Use underwater, constant water pools, on damp substrates or in trafficable areas
- Use where abrasion of physical abuse can be expected
- Use of sealing submerged joints
- Use in external applications where rain is imminent within 4 hours

### CLEANING

Clean off excess with a damp cloth or water immediately. Use Bostik Handy Wipe towels to remove adhesive from skin.

# BOSTIK GAP SEAL

## STORAGE AND SHELF LIFE

Store in cool (between 5°C to 25°C) dry, well-ventilated area out of direct sunlight. Store away from oxidizing agents and acids. Shelf life is 24 months in original unopened container if stored below 25°C.

## DISPOSAL

Empty cartridges may be disposed via local landfill. If spilt, absorb with clay, sand or earth. Collect and seal in properly labeled metal container. Dispose of according to local authority regulations. Do not dispose of down drains or into local waterways.

## VOC INFORMATION

21g/litre

## HEALTH AND SAFETY

Non-hazardous.

If poisoning occurs, contact Poisons Information Centre.

## FIRST AID

**Swallowed:** Do not induce vomiting, give a glass of water and contact a doctor immediately.

**Skin:** If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

**Inhaled:** Remove from contaminated area.

**Eyes:** Hold eyes open and flood with water for at least 15 minutes.

**For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.**

BOSTIK HOTLINE

Smart help 1800 898 551



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit [www.bostik.com/au](http://www.bostik.com/au)