



SAFETY DATA SHEET

BOSTIK ISR 70-05 AP BLACK
Revision Number 1.01

Revision date 26-Apr-2022
Supersedes Date: 31-Jul-2017

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name BOSTIK ISR 70-05 AP BLACK

Product Code(s)

30600968
30601075; 30622703; 30622701; 30622702; 30621890; 30622704; 30600968

Other means of identification

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Adhesives and/or sealants

Uses advised against No information available

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

Manufacturer

Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Serious eye damage/eye irritation	Category 2 - (H319)
--	---------------------

Label elements

Exclamation mark



Signal word

SAFETY DATA SHEET

BOSTIK ISR 70-05 AP BLACK
Revision Number 1.01

Revision date 26-Apr-2022
Supersedes Date: 31-Jul-2017

WARNING

Hazard statements

H319 - Causes serious eye irritation

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Other hazards which do not result in classification

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
Trimethoxyvinylsilane	2768-02-7	0 - <10
1-Propanamine, 3-(trimethoxysilyl)-	13822-56-5	0 - <10
Carbon black	1333-86-4	0 - <10
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	0 - <10
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a physician.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contact Wash skin with soap and water.

Ingestion Call a physician immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Small amounts of toxic methanol are released by hydrolysis.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET

BOSTIK ISR 70-05 AP BLACK
Revision Number 1.01

Revision date 26-Apr-2022
Supersedes Date: 31-Jul-2017

Symptoms None known.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable Extinguishing Media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Silicon dioxide.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.

SAFETY DATA SHEET

BOSTIK ISR 70-05 AP BLACK
Revision Number 1.01

Revision date 26-Apr-2022
Supersedes Date: 31-Jul-2017

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feeding stuffs.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C. Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Chemical name	Australia
Carbon black 1333-86-4	TWA: 3 mg/m ³

OEL as published by Safe Work Australia

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection If splashes are likely to occur, wear safety glasses with side-shields.

Skin and body protection Wear suitable protective clothing.

Hand protection Wear suitable gloves.

Respiratory protection Organic gases and vapors filter conforming to EN 14387. White. Brown.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Solid
Appearance Paste
Color Black
Odor Odorless
Odor threshold Not applicable

Property	Values	Remarks • Method
pH	No data available	
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	No data available	
Flash point	No data available	
Evaporation rate	No data available	
Flammability	Not applicable for liquids	
Flammability Limit in Air		
Upper flammability or explosive	No data available	

SAFETY DATA SHEET

BOSTIK ISR 70-05 AP BLACK
Revision Number 1.01

Revision date 26-Apr-2022
Supersedes Date: 31-Jul-2017

limits	
Lower flammability or explosive limits	No data available
Vapor pressure	No data available
Relative vapor density	No data available
Relative density	No data available
Water solubility	Insoluble in water
Solubility(ies)	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	17000 - 32000 Pa.s @ 20 °C
Explosive properties	No information available
Oxidizing properties	No information available
Other information	
Solid content (%)	No information available
Density	1.5 g/ml
VOC Content (%)	No information available

Section 10: Stability and reactivity

Reactivity

Reactivity Product cures with moisture.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Incompatible materials None known based on information supplied.

Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

SAFETY DATA SHEET

BOSTIK ISR 70-05 AP BLACK
Revision Number 1.01

Revision date 26-Apr-2022
Supersedes Date: 31-Jul-2017

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Based on available data, the classification criteria are not met. May cause irritation. Prolonged contact may cause redness and irritation. May cause sensitization in susceptible persons.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	May cause redness and tearing of the eyes.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg
ATEmix (inhalation-vapor) 482.40 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
1-Propanamine, 3-(trimethoxysilyl)-	LD50 (Rattus) > 2000 mg/ kg (2,97 ml/kg) (OECD 401)	LD50 (Oryctolagus cuniculus) > 2000 mg/kg 11,3 ml/kg) OECD 402	-
Carbon black	LD50 > 8000 mg/kg (Rattus) OECD 401	> 3 g/kg (Oryctolagus cuniculus)	> 4.6 mg/m ³ (Rat) 4 h
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	LD50 (Rattus) > 2000 mg/kg OECD 423	LD50 (Rattus) > 3 170 mg/kg OECD 402	=500 mg/m ³ (Rattus) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

SAFETY DATA SHEET

BOSTIK ISR 70-05 AP BLACK
Revision Number 1.01

Revision date 26-Apr-2022
Supersedes Date: 31-Jul-2017

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		72 hours	irritant

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			Eye Damage

Respiratory or skin sensitization OECD Test No. 406: Skin Sensitization. No sensitization responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitization in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization	Guinea pig	Dermal	No sensitization responses were observed

Component Information			
Trimethoxyvinylsilane (2768-02-7)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization, Buehler test	Guinea pig	Dermal	sensitizing

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization	Guinea pig	Dermal	Did not cause sensitization on laboratory animals

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization	Guinea pig		No sensitization responses were observed

Germ cell mutagenicity No information available.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
Carbon black 1333-86-4			Group 2B

Legend

IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans

Reproductive toxicity No information available.

SAFETY DATA SHEET

BOSTIK ISR 70-05 AP BLACK
Revision Number 1.01

Revision date 26-Apr-2022
Supersedes Date: 31-Jul-2017

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)		
Method	Species	Results
OECD Test No. 408: Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	Not Classifiable

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)		
Method	Species	Results
OECD Test No. 414: Prenatal Development Toxicity Study	Rat, Rabbit	Reproductive toxicant

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Subchronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapor		90 days	0.058 NOAEL

Aspiration hazard No information available.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	EC50 (72h) > 1000 mg/l (Desmodesmus subspicatus) EU Method C.3 (Algal Inhibition test)	LC50 (96h) > >934 mg/L (Danio rerio) OECD 203	-	EC50 (48h) = 331 mg/L (Daphnia magna) OECD 202
Carbon black 1333-86-4	>10000 mg/l (Desmodesmus subspicatus) OECD 202	>1000 mg/l (Brachydanio rerio) OCDE 203	-	EC50: >5600mg/L (24h, Daphnia magna)
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	EC50 72Hr 0.705 mg/l (Pseudokirchnerella subcapitata)	LC50 (96h) = 5.29 mg/l (Oryzias latipes)	-	LC50 48Hr 8.58 mg/l (Daphnia magna)

Persistence and degradability

Persistence and degradability No information available.

SAFETY DATA SHEET

BOSTIK ISR 70-05 AP BLACK
Revision Number 1.01

Revision date 26-Apr-2022
Supersedes Date: 31-Jul-2017

Component Information			
Trimethoxyvinylsilane (2768-02-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)			
Method	Exposure time	Value	Results
OECD Test No. 301A: Ready Biodegradability: DOC Die-Away Test (TG 301 A)	28 days		67 % Not readily biodegradable

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)			
Method	Exposure time	Value	Results
OECD Test No. 303: Simulation Test - Aerobic Sewage Treatment -- A: Activated Sludge Units; B: Biofilms	28 days	Total organic carbon (TOC)	24 % Moderate

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Trimethoxyvinylsilane 2768-02-7	1.1
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	0.35

Mobility

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

Section 14: Transport information

ADG Not regulated

IATA Not regulated

IMDG Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SAFETY DATA SHEET

BOSTIK ISR 70-05 AP BLACK
Revision Number 1.01

Revision date 26-Apr-2022
Supersedes Date: 31-Jul-2017

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

International Inventories

AICS	Listed
NZIoC	Listed
ENCS	Listed
IECSC	Not Listed
KECL	Listed
PICCS	Not Listed

Legend:

- AICS** - Australian Inventory of Chemical Substances
- NZIoC** - New Zealand Inventory of Chemicals
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Revision date 26-Apr-2022

SAFETY DATA SHEET

BOSTIK ISR 70-05 AP BLACK
Revision Number 1.01

Revision date 26-Apr-2022
Supersedes Date: 31-Jul-2017

Revision Note

SDS sections updated. 13.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet