

# **Hazardous Chemical, Dangerous Goods**

### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Megapoxy E155 - Part B

Recommended use: Liquid epoxy for use in electrical industries

Supplier: Vivacity Engineering Pty Ltd

**ABN:** 78 305 545 664 **Street Address:** 3 Sefton Road

Thornleigh NSW 2120 Australia

**Telephone:** +61 2 9875 3044

Email:sales@megapoxy.comEmail:info@megapoxy.com

Emergency Telephone number: +61 2 9875 3044

### 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia GHS 7.





#### Signal Word

Danger

## **Hazard Classifications**

Acute Toxicity - Oral - Category 4
Skin Corrosion/Irritation - Category 1B
Serious Eye Damage/Irritation - Category 1

Sensitisation - Skin - Category 1

Chronic Hazard to the Aquatic Environment - Category 3

#### **Hazard Statements**

H302 Harmful if swallowed. H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

## **Prevention Precautionary Statements**

P261 Avoid breathing dust, fume, gas, mist, vapours or spray.

P264 Wash hands, face and all exposed skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective clothing, gloves, eye/face protection and suitable respirator.

#### **Response Precautionary Statements**

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower.

Product Name: Megapoxy E155 - Part B Reference No:

Issued: 2022-11-16 Version: 2.0 Page 1 of 8



P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

# **Storage Precautionary Statement** P405 Store locked up.

### **Disposal Precautionary Statement**

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

Poison Schedule: S5. Caution

#### DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

**Dangerous Goods Class:** 8

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
1,2-Ethanediamine, N,N'-bis(2-aminoethyl)- Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- Ingredients determined to be Non-Hazardous	112-24-3 2855-13-2	10-29 % 30-60 % Balance

100%

#### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin Contact:** Effects may be delayed. This material, or a component of the material, can be absorbed through the skin with resultant toxic effects. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye contact:** Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor.

**PPE for First Aiders:** Wear safety shoes, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking,

Product Name: Megapoxy E155 - Part B Reference No:

Issued: 2022-11-16 Version: 2.0 Page 2 of 8



eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed. Can cause corneal burns.

#### 5. FIRE FIGHTING MEASURES

Hazchem Code: 2X

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Non-combustible material.

Fire fighting further advice: Not applicable.

### 6. ACCIDENTAL RELEASE MEASURES

#### **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

#### **LARGE SPILLS**

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

**Dangerous Goods - Initial Emergency Response Guide No: 36** 

#### 7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 8 Corrosive as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

This material is a Scheduled Poison Schedule 5 (Caution) and must be stored, maintained and used in accordance with the relevant regulations.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Natural ventilation should be adequate under normal use conditions.

Product Name: Megapoxy E155 - Part B

Issued: 2022-11-16

Version: 2.0

Reference No:
Page 3 of 8



Personal Protection Equipment: SAFETY SHOES, GLOVES, SAFETY GLASSES.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear safety shoes, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid
Colour: Clear to Pale
Odour: Amine

**Solubility:** Miscible in water and other solvents

**Specific Gravity (20 °C):** 0.94-0.98 @ 25 Deg C

Relative Vapour Density (air=1): 7

Vapour Pressure (20 °C):<0.01 Pa</th>Flash Point (°C):112 Deg CFlammability Limits (%):lower: 1.2Autoignition Temperature (°C):380 Deg CBoiling Point/Range (°C):247 Deg CDecomposition Point (°C):>200 Deg C

pH: 11.6
Total VOC (g/Litre): Nil
% Volatile by Volume: Nil

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

## 10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Acute Effects** 

Product Name: Megapoxy E155 - Part B Reference No:

Issued: 2022-11-16 Version: 2.0 Page 4 of 8



Reference No:

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

**Skin contact:** Harmful in contact with skin. Can be absorbed through the skin with resultant toxic effects. Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

**Ingestion:** Harmful if swallowed. Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.

**Eye contact:** A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

#### **Acute toxicity**

**Inhalation:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): LC50 > 20.0 mg/L for vapours or LC50 > 5.0 mg/L for dust and mist or LC50 > 20,000 ppm for gas

**Skin contact:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

**Ingestion:** This material has been classified as a Category 4 Hazard. Acute toxicity estimate (based on ingredients): 300 - 2,000 mg/Kg bw

**Corrosion/Irritancy:** Eye: this material has been classified as a Category 1 Hazard (irreversible effects to eyes). Skin: this material has been classified as a Category 1B Hazard (irreversible effects to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

**Chronic Toxicity** 

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

**Specific target organ toxicity (repeat exposure):** This material has been classified as non-hazardous.

# 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

**Long-term aquatic hazard:** This material has been classified as a Category Chronic 3 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 10 - 100 mg/L, where the substance is not rapidly degradable and/or BCF  $\geq 500 \text{ and/or log K}_{ow} \geq 4$ .

Ecotoxicity: No information available.

Product Name: Megapoxy E155 - Part B

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Issued: 2022-11-16 Version: 2.0 Page 5 of 8



**Mobility:** No information available.

#### 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

### 14. TRANSPORT INFORMATION

#### **ROAD AND RAIL TRANSPORT**

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



UN No: 2735 **Dangerous Goods Class:** 

Subsidiary Risk, Secondary Subsidiary:

Packing Group: Ш **Special Provisions:** 223, 274 **Limited Quantities:** 5 L **Hazchem Code:** 2X **Emergency Response Guide No:** 36

Packagings and IBCs

**Packing Instructions** P001, LP01

**Special Packing Provisions** 

**Portable Tanks and Bulk Containers** 

Instructions

**Special Provisions** TP1, TP28

**Proper Shipping Name:** AMINES, LIQUID, CORROSIVE, N.O.S.

(Cyclohexanemethanamine, 5-amino-1,3,3trimethyl- & 1,2-Ethanediamine, N,N'-bis(2-

aminoethyl)-)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2), radioactive substances (Class 7) or food and food packaging in any quantity. Note 1: Concentrated strong alkalis are incompatible with concentrated strong acids. Note 2: Concentrated strong acids are incompatible with concentrated strong alkalis. Note 3: Acids are incompatible with Dangerous Goods of Class 6 which are cyanides. Exemptions may apply.

#### MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



Product Name: Megapoxy E155 - Part B Reference No:

Issued: 2022-11-16 Version: 2.0 Page 6 of 8



UN No: 2735 Dangerous Goods Class: 8

Subsidiary Risk, Secondary Subsidiary:

Packing Group:

Special Provisions:

Limited Quantities:

Hazchem Code:

Emergency Response Guide No:

EMS fire:

F-A

EMS spill:

Substituty Substituty

III

223, 274

2X

2X

Emergency Response Guide No:

S-B

Packagings and IBCs

Packing Instructions: P001, LP01

**Special Packing Provisions:** 

**Portable Tanks and Bulk Containers** 

Instructions:

Special Provisions: TP1, TP28

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S.

(Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- & 1,2-Ethanediamine, N,N'-bis(2-

aminoethyl)-))

#### **AIR TRANSPORT**

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



**UN No:** 2735

Dangerous Goods Class: 8

Subsidiary Risk, Secondary Subsidiary:

Packing Group: III
Special Provisions: A3
ERG Code: 8L

Passengers and Cargo Aircraft Limited

Quantities

Packing Instructions: Y818
Maximum Net Quantity per Package: 1 L

**Passengers and Cargo Aircraft** 

Packing Instructions: 818
Maximum Net Quantity per Package: 5 L

Cargo Aircraft Only

Issued: 2022-11-16

Packing Instructions: 820
Maximum Net Quantity per Package: 60 L

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S.

(Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- & 1,2-Ethanediamine, N,N'-bis(2-

aminoethyl)-))

# 15. REGULATORY INFORMATION

### This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Product Name: Megapoxy E155 - Part B Reference No:

Version: 2.0 Page 7 of 8



International Convention for the Prevention of Pollution from Ships (MARPOL)

## This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

· Wastes from production, formulation and use of resins, latex, plasticizers, glues/adhesives

### This material/constituent(s) is covered by the following requirements:

- The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth).
- All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

### **16. OTHER INFORMATION**

Reason for issue: Revised

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

Product Name: Megapoxy E155 - Part B Reference No:

Issued: 2022-11-16 Version: 2.0 Page 8 of 8