

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version 2.4 Revision Date: 15.03.2017 SDS Number: 826254-00009 Date of last issue: 12.10.2016
Date of first issue: 25.11.2014

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : DOW CORNING(R) 890-SL SILICONE JOINT SEALANT
Product code : 000000000004105659

Manufacturer or supplier's details

Company : Dow Corning Australia Pty Ltd, ABN 36 008 444 166

Address : **Darling Park, Tower 2
Level 20, 201 Sussex Street
Sydney. NSW 2000**

**Locked Bag 2095
North Ryde, NSW 1670**

Telephone : 1300-369-745

Emergency telephone number : **1300-360-732 (24 Hours)**

Telefax : 1300-650-785

Recommended use of the chemical and restrictions on use

Recommended use : Construction materials and additives

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Serious eye damage/eye irritation : Category 2A

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear eye protection/ face protection.

Response:

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Silicone elastomer

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Calcium carbonate	471-34-1	>= 30 -< 60
Methylvinyl bis(N-ethylacetamido)silane	87855-59-2	< 10
Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine	68952-53-4	< 10
Quartz	14808-60-7	< 10
N-ethylacetamide	625-50-3	< 10
Octamethylcyclotetrasiloxane	556-67-2	< 10
Impurities in methylvinylbis(N-ethylacetamido)silane	Not Assigned	< 10

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Silicon oxides
Formaldehyde
Nitrogen oxides (NO_x)
Metal oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid inhalation of vapour or mist.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

Conditions for safe storage : Keep in properly labelled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version 2.4 Revision Date: 15.03.2017 SDS Number: 826254-00009 Date of last issue: 12.10.2016
 Date of first issue: 25.11.2014

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	TWA	10 mg/m ³ (Calcium carbonate)	AU OEL
	Further information: This value is for inhalable dust containing no asbestos and < 1% crystalline silica			
Quartz	14808-60-7	TWA (Respirable dust)	0.1 mg/m ³	AU OEL
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	US WEEL

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Calcium carbonate

Quartz

Engineering measures : Processing may form hazardous compounds (see section 10).
 Ensure adequate ventilation, especially in confined areas.
 Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type

Hand protection
 Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : Charcoal
- Odour : Fishy
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : > 35 °C
- Flash point : 100 °C
Method: Pensky-Martens closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable
- Flammability (liquids) : Not applicable
- Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Relative density : 1.3

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : 300000 mm²/s (25 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Use at elevated temperatures may form highly hazardous compounds.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products
Thermal decomposition : Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation
Skin contact
Ingestion
Eye contact

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version 2.4 Revision Date: 15.03.2017 SDS Number: 826254-00009 Date of last issue: 12.10.2016
Date of first issue: 25.11.2014

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**Calcium carbonate:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Methylvinyl bis(N-ethylacetamido)silane:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Expert judgement

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: On basis of test data.

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

N-ethylacetamide:

Acute oral toxicity : LD50 (Rat): 3,950 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC0 (Rat): 2.19 mg/l
Exposure time: 8 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

- Acute oral toxicity : LD50 (Rat): > 4,800 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: On basis of test data.
- Acute inhalation toxicity : LC50 (Rat): 2975 ppm
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: On basis of test data.
- Acute dermal toxicity : LD50 (Rabbit): > 2.5 ml/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: On basis of test data.

Impurities in methylvinylbis(N-ethylacetamido)silane:

- Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Expert judgement
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:**Calcium carbonate:**

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Methylvinyl bis(N-ethylacetamido)silane:

Species: Rabbit
Result: No skin irritation
Remarks: On basis of test data.

Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine:

Result: Skin irritation
Remarks: Based on data from similar materials

N-ethylacetamide:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

Octamethylcyclotetrasiloxane:

Species: Rabbit
Result: No skin irritation
Remarks: On basis of test data.

Impurities in methylvinylbis(N-ethylacetamido)silane:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Calcium carbonate:**

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Methylvinyl bis(N-ethylacetamido)silane:

Species: Rabbit
Result: Irreversible effects on the eye
Remarks: On basis of test data.

Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine:

Result: Irritation to eyes, reversing within 21 days
Remarks: Based on data from similar materials

N-ethylacetamide:

Species: Rabbit
Result: No eye irritation
Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

Species: Rabbit
Result: No eye irritation
Remarks: On basis of test data.

Impurities in methylvinylbis(N-ethylacetamido)silane:

Species: Rabbit
Result: Irreversible effects on the eye
Remarks: Based on data from similar materials

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version 2.4 Revision Date: 15.03.2017 SDS Number: 826254-00009 Date of last issue: 12.10.2016
Date of first issue: 25.11.2014

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Calcium carbonate:

Test Type: Local lymph node assay (LLNA)
Exposure routes: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative

Methylvinyl bis(N-ethylacetamido)silane:

Assessment: Does not cause skin sensitisation.

Test Type: Buehler Test
Species: Guinea pig
Result: negative
Remarks: On basis of test data.

N-ethylacetamide:

Test Type: Intracutaneous test
Exposure routes: Skin contact
Species: Guinea pig
Result: negative
Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

Assessment: Does not cause skin sensitisation.

Test Type: Maximisation Test
Species: Guinea pig
Result: negative
Remarks: On basis of test data.

Impurities in methylvinylbis(N-ethylacetamido)silane:

Assessment: Does not cause skin sensitisation.

Test Type: Buehler Test
Species: Guinea pig
Result: negative
Remarks: Based on data from similar materials

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version 2.4 Revision Date: 15.03.2017 SDS Number: 826254-00009 Date of last issue: 12.10.2016
Date of first issue: 25.11.2014

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Components:**Calcium carbonate:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Methylvinyl bis(N-ethylacetamido)silane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: On basis of test data.

: Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: On basis of test data.

N-ethylacetamide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: On basis of test data.

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: On basis of test data.

: Test Type: Mutagenicity (in vitro mammalian cytogenetic test)
Result: negative
Remarks: On basis of test data.

: Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: On basis of test data.

: Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative
Remarks: On basis of test data.

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version 2.4	Revision Date: 15.03.2017	SDS Number: 826254-00009	Date of last issue: 12.10.2016 Date of first issue: 25.11.2014
----------------	------------------------------	-----------------------------	---

- Genotoxicity in vivo
- : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative
Remarks: On basis of test data.
 - : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: On basis of test data.
 - : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: On basis of test data.
- Germ cell mutagenicity - Assessment
- : Animal testing did not show any mutagenic effects.

Impurities in methylvinylbis(N-ethylacetamido)silane:

- Genotoxicity in vitro
- : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials
 - : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:**Quartz:**

Species: Humans
Application Route: inhalation (dust/mist/fume)
Result: positive
Remarks: IARC: (International Agency for Research on Cancer)
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

- Carcinogenicity - Assessment
- : Positive evidence from human epidemiological studies (inhalation)

N-ethylacetamide:

Species: Mouse
Application Route: inhalation (vapour)
Exposure time: 18 Months
Result: negative

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

Remarks: Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:**Calcium carbonate:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Methylvinyl bis(N-ethylacetamido)silane:

Effects on fertility : Species: Rat, male
Application Route: Ingestion
Symptoms: Effects on fertility
Remarks: On basis of test data.

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

N-ethylacetamide:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Mouse
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

Octamethylcyclotetrasiloxane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat, male and female
Application Route: inhalation (vapour)
Symptoms: Effects on fertility
Remarks: On basis of test data.

Effects on foetal development : Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rabbit

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

Application Route: inhalation (vapour)
Symptoms: No effects on foetal development
Remarks: On basis of test data.

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

Impurities in methylvinylbis(N-ethylacetamido)silane:

Effects on fertility : Species: Rat, male
Application Route: Ingestion
Symptoms: Effects on fertility
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:**Quartz:**

Exposure routes: inhalation (dust/mist/fume)
Target Organs: Lungs
Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Octamethylcyclotetrasiloxane:

Exposure routes: Ingestion
Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Exposure routes: inhalation (vapour)
Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Exposure routes: Skin contact
Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Repeated dose toxicity**Components:****Calcium carbonate:**

Species: Rat
NOAEL: 1,000 mg/kg
Application Route: Ingestion

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

Exposure time: 6 Weeks
Method: OECD Test Guideline 422

Quartz:

Species: Humans
LOAEL: 0.053 mg/m³
Application Route: Inhalation
Remarks: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

N-ethylacetamide:

Species: Rabbit
NOAEL: 0.09 mg/l
LOAEL: 0.36 mg/l
Application Route: inhalation (vapour)
Exposure time: 24 Months
Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

Species: Rat
Application Route: Ingestion
Remarks: On basis of test data.

Species: Rat
Application Route: inhalation (vapour)
Remarks: On basis of test data.

Species: Rabbit
Application Route: Skin contact
Remarks: On basis of test data.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Further information**Components:****Octamethylcyclotetrasiloxane:**

Remarks: Results from a 2 year repeated vapour inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version 2.4 Revision Date: 15.03.2017 SDS Number: 826254-00009 Date of last issue: 12.10.2016
Date of first issue: 25.11.2014

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity**Components:****Calcium carbonate:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): > 14 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Methylvinyl bis(N-ethylacetamido)silane:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- NOEC (Oncorhynchus mykiss (rainbow trout)): 50 mg/l
Exposure time: 96 h
- LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 69 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h

Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine:**Ecotoxicology Assessment**

- Acute aquatic toxicity : No toxicity at the limit of solubility

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

Quartz:**Ecotoxicology Assessment**

Acute aquatic toxicity : No toxicity at the limit of solubility

Chronic aquatic toxicity : No toxicity at the limit of solubility

N-ethylacetamide:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 3,390 mg/l
 Exposure time: 96 h
 Method: DIN 38412
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 580 mg/l
 Exposure time: 48 h
 Method: DIN 38412
 Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 500 mg/l
 Exposure time: 96 h
 Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 10,000 mg/l
 Exposure time: 17 h
 Method: DIN 38 412 Part 8
 Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): > 0.0063 mg/l
 Exposure time: 336 h
 Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EC50 (Mysidopsis bahia (opossum shrimp)): > 0.0091 mg/l
 Exposure time: 96 h
 Remarks: No toxicity at the limit of solubility

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.022 mg/l
 Exposure time: 72 h
 Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): >= 0.0044 mg/l
 Remarks: On basis of test data.
 No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 0.0079 mg/l
 Exposure time: 21 d
 Remarks: On basis of test data.
 No toxicity at the limit of solubility

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version 2.4 Revision Date: 15.03.2017 SDS Number: 826254-00009 Date of last issue: 12.10.2016
Date of first issue: 25.11.2014

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Persistence and degradability**Components:****Methylvinyl bis(N-ethylacetamido)silane:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 62.66 %
Method: OECD Test Guideline 301B

Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine:

Biodegradability : Result: Not readily biodegradable.
Remarks: Based on data from similar materials

N-ethylacetamide:

Biodegradability : Result: Inherently biodegradable.
Biodegradation: 100 %
Exposure time: 6 d
Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 3.7 %
Exposure time: 28 d
Method: OECD Test Guideline 310

Stability in water : Degradation half life: 69.3 - 144 h (24.6 °C) pH: 7
Method: OECD Test Guideline 111

Bioaccumulative potential**Components:****Octamethylcyclotetrasiloxane:**

Bioaccumulation : Species: Pimephales promelas (fathead minnow)
Bioconcentration factor (BCF): 12,400

Partition coefficient: n-octanol/water : log Pow: 6.48 (25.1 °C)

Mobility in soil

No data available

Other adverse effects**Components:****Octamethylcyclotetrasiloxane:**

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

Results of PBT and vPvB assessment : Remarks: Octamethylcyclotetrasiloxane (D4) meets the current REACh Annex XIII criteria for PBT and vPvB. In Canada, D4 has been assessed and deemed to meet the PiT criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations**UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Licensing Requirements : There is no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

legislation.

The components of this product are reported in the following inventories:

- NZIoC : All ingredients listed or exempt.
- REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
- TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
- AICS : All ingredients listed or exempt.
- IECSC : One or more components of this product may not be listed on the IECSC inventory, but this component(s) is (are) registered with volume limitation under Dow Corning entity in China. Consult your local Dow Corning office.
- KECI : All ingredients listed, exempt or notified.
- PICCS : Consult your local Dow Corning office.
- DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
- ENCS/ISHL : Consult your local Dow Corning office.
- TCSI : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Further information

- Revision Date : 15.03.2017
- Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

- Date format : dd.mm.yyyy

DOW CORNING(R) 890-SL SILICONE JOINT SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 12.10.2016
2.4	15.03.2017	826254-00009	Date of first issue: 25.11.2014

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
AU OEL	:	Australia. Workplace Exposure Standards for Airborne Contaminants.
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	:	8-hour, time-weighted average
AU OEL / TWA	:	Exposure standard - time weighted average
US WEEL / TWA	:	Time weighted average

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN