



SEKISUI FOAM AUSTRALIA

1 – 5 Parraweena Road, Taren Point
NSW 2229 AUSTRALIA
T: +61 2 9525 9880 E: info@sekisuifoam.com.au

TECHNICAL INFORMATION

TECHNICAL DATA SHEET

Sof-FormTM Expansion Joint

Description:

Sof-FormTM Expansion Joint is a foam based material with optional adhesive backing. It incorporates Softlon[®], a closed cell, electron beam crosslinked, polyolefin foam with an outer skin. Sof-FormTM Expansion Joint is free of heavy metals, plasticisers and CFCs.

| Property | Typical Value | Test Method |
|------------------------------|--|-------------|
| Density | 25 kg/m³ (nominal) | Internal |
| Tensile Strength | 3.3 kg/cm² (longitudinal) | JIS K6767 |
| | 1.8 kg/cm² (crosswise) | |
| Elongation | 240% (longitudinal) | JIS K6767 |
| | 140% (crosswise) | |
| Tear Strength | 2.0 kg/cm (longitudinal) | JIS K6767 |
| | 1.3 kg/cm (crosswise) | |
| Compression Strength | 0.30 kg/cm ² @ 25% deflection | Internal |
| | 0.85 kg/cm ² @ 50% deflection | |
| Hot Sealant Penetration | Zero | RTA T1154 |
| Extrusion during Compression | 1.3 mm | ASTM D545 |
| Recovery after Compression | 100% after 10 minutes | ASTM D545 |
| Water Absorption | 0.09 mg/cm ² | JIS K6767 |
| Water Vapour Permeability | 5.7 x 10 ⁻¹⁴ kg/s.m.Pa | ASTM E96 |



This information on Sekisui Foam International products is presented to the best of our knowledge. All product data is based on average values and is for guidance only. As these products are subject to constant research and development, we reserve the right to update the contents without notice.



Recommendations as to methods of post fabrication, application and use of Sekisui Foam International products are based on our experience and knowledge of the characteristics of our products and are given in good faith. As producer of the material we have no control over the application of Sekisui Foam International products and no legal responsibility is accepted for such recommendations. In particular, no responsibility is accepted by us for any system in which Sekisui Foam International products are utilised or for any application.



Softlon and **Thermobreak** – Registered trademarks of Sekisui Chemical Co. Ltd or its subsidiaries.

 $\hbox{@}$ Sekisui Pilon Pty Ltd. Date of Publication: January 2016.